# SAFETY

Should be the first consideration of every employee.

Every unsafe condition and practice should be reported promptly to immediate superior or other proper person.

# CHICAGO & WESTERN INDIANA RAILROAD COMPANY

TIME TABLE No. 14

IN EFFECT

SUNDAY, OCTOBER 28, 1962

AT 12:01 A. M. CENTRAL STANDARD TIME

Superseding all previous Time Tables and Supplements

No. 14

This Time Table is for the Government and Information of Employes only

Note Important Changes in Special Instructions and Train Numbers

Read the rules and study the table carefully

R. E. McMILLAN General Manager

> M. SWISLOW Superintendent

## MAIN LINE STATIONS

	Dispatchers	Other	Interlocking Station	Interlocking Signals	Switch	Train Order Signal	RAILROAD JUNCTION OR CROSSING
Chicago Dearborn Station	x	x					
Roosevelt Road		X	X	X	X		Charles of the same
15th St.	X	X	X	X			AT&SF Yard Connections
16th St.	X	X	X	X			STATE OF THE PARTY
21st St.	X	X	X	X			AT&SF-IC-Penna.
40th St.	X	X	X	X		900	Penna. C. J.
47th St.	X	X	X	X	53		GTW-C,J.
Ford St.	X	X	X	X			Penna.
Englewood	X	X					\$200 E. S.
74th St.	X	X	X	X			Wabash-BRC
80th St.	X	X			X		Dolton Branch-BRC
81st St.	X	X	X	X		X	Dolton Branch
Pullman Junction	X	X			X	X	NKP-BRC-CRI&P
South Deering		X		X			CSL-BRC
Main Line Bridge	x	x	x	x			
Ford Crossover		X					NKP-CSS&SB
Burnham	×	X	x	X			Penna-CSS&SB-C&O
State Line	X	X	X	X		X	BOCT-Monon-Erie-IHB NKP-C&O
South Hammond	X		1	1			Monon

## DOLTON BRANCH STATIONS

80th St.	X	X			X		Main Line-BRC
81st St.	X	X	X	X		X	Main Line
Oakdale		X		X			CRI&P
Dolton Junction	X	X	X	X.			Penna-IHB-BOCT
Yard Center	X	- 10				X	C&EI

J. J. MORIARTY	.Supervising Trainmaster
M. F. HILL	.Trainmaster
J. M. PHILLIPS	Francisco of Franksis
E. P. HENRY	. Chief Train Dispatcher
D. H. CAMP	. Dispatcher
R. V. PEIRSON	. Dispatcher
M. W. ANDERSON	. Dispatcher
Dispatchers Phone - HA 7-7514	

U. IN	1. Maioney
	Office—Dearborn St. Station—Telephone HArrison 7-7500
	Residence—7300 So. Shore Drive—REgent 1-5928
E. P	. Holland
	Office—Dearborn St. Station—Telephone HArrison 7-7500
	Residence—7953 S. Manistee Ave.—Telephone SO Shore 8-3714

Office—2652 W. 59th St.—Telephone PRospect 6-5577

Residence—5842 Stony Island Ave.—DOrchester 3-3309

## HOSPITAL AND AMBULANCE SERVICE

Cases of injuries or fatalities to persons other than employees or fatal accidents to employees must be turned over to the municipal police in every instance.

In case of personal injury to an employee necessitating ambulance service it is desired that Cassidy Ambulance Service, telephone KEdzie 3-2864 or KEdzie 3-2865, be called promptly to take injured person to the Illinois Central Hospital, 5800 South Stony Island Avenue, telephone Midway 3-9200. In extreme emergency injured person will be taken to the nearest hospital.

When ambulance service is not required, in all cases of personal injury, employes should be sent to Dr. Westline's office, 2652 West 59th Street, Phone PRospect 6-5577. Office hours are as follows:

Monday to Friday-9 A. M. C. S. T. to 5 P. M. C. S. T.

During hours when Dr. Westline's office is closed injured persons should be sent to the Illinois Central Hospital.

These injuries should be reported at once to Office of Superintendent of Police at Clearing, telephone Portsmouth 7-1000 on week days between 7:00 A. M. and 11 P. M. and Portsmouth 7-6476 on week days between 11:00 P. M. and 7:00 A. M. and on Sundays and Holidays, who will notify Claim Department.

These matters will be handled with the Train Dispatcher under any conditions that this may expedite the call.

				FII	RST CLA	SS
		icago	419	221	305	111
Telephone Stations	STATIONS	Distance from Chicago	Santa Fe 19 Pass.	G. T. W. 20 Pass.	Monon 5 Pass.	Wab. 111 Pass.
Telephi		Distan	DAILY	DAILY	DAILY	DAILY
-N	LvCHICAGO		A. M. 9.00	A. M. 9.30	A. M. 10.00	A. M. 10-30
-N	A. T. & S. F. JCT	1.3	9.05	9.35	10.05	10.35
-N	40TH ST	3.7		9.38	10.08	10.38
-N	47TH ST	4.6		9.39	10.09	10.39
	49TH ST. (G. T. Conn.)	4.9		9.40		
	55TH ST	5.6				
	FORD ST. (59th ST.)	6.0		- 11	10.12	10.42
-N	ENGLEWOOD	6.6			s10.14	s10.44
-N	74th ST. JCT. (Hamilton Pk.)	7.9			10.16	10.47
	AUBURN PARK (79TH ST.)	8.7				
-N	81ST ST	9.0			10.18	
-N	PULLMAN JCT	12.3			10.23	
	.SO. DEERING (112th St.).	15.0			10.27	
-N	MAIN LINE BRIDGE	16.5			10.29	
	FORD CROSSOVER	17.6			10.30	
-N	BURNHAM	18.2			10.31	
-N	STATE LINE	19.8			10.33	
-N	HAMMOND	20.8			s10.38	
-N	ArSO. HAMMOND	23.3			10.42	
	OAKDALE	10.1				
_	EUCLID PARK	11.0				
	FERNWOOD	11.7				
	ROSELAND	12.2				
	ROSELAND	12.7				
		13.2				
	KENSINGTON	13.6				
5	DOLTON	16.6				
D -N	DOLTON JCT	16.8				
-N	ArYARD CENTER	18.0				
			A. M.	A. M.	A. M.	A. M.
	Figures between Stations show Distances		DAILY	DAILY	DAILY	DAILY

Northward trains are superior to trains of the same class in opposite direction on single track only.

The following signs indicate:—s Regular Stop; f Flag Stop; D Day; N Night.

400	455	71	105	401	02	121	75
423					93		
Santa Fe 123	Erie 6	C. & W. I.	C. & W. I.	Santa Fe	C. & E. I.	Wab. 121	C. & W. I.
Pass.	Pass.	Pass.	Pass.	Pass.	Pass.	Pass.	Pass.
DAILY	DAILY	Daily except Sat. & Sun	Saturday only	DAILY	DAILY	DAILY	Daily except Sat. & Sun
A. M. 11.00	A. M. 11-10	A. M. 11.35	P. M. 1 - 10	P M 3.15	P. M. 3.45	P. M. 4-50	P.M. 5.25
11.05	11.15	11.40	1.15	3.20	3.50	4.55	5.30
	11.18	11.44	1.19		3.53	4.58	5.33
	11.19	f11.45	s 1.20		3.54	4.59	s 5.35
		f11.49	s 1.23				s 5.38
	11.22				3.57	5.02	
	s11.24	s11.51	s 1.26		s 3.59	s 5.04	s 5.42
	11.26	f11.56	s 1.30		4.01	5.07	s 5.48
		f11.58	s 1.33				s 5.51
	11.28		1.34		4.03		5.53
	11.33						
	11.37						
	11.39						
	11.40						
	11.41						
	11.43						
		s12.02			4.06		s 5.57
		s12.04	s 1.38				s 5.59
		s12.06					s 6.01
		s12.07	s 1.41				s 6.03
		s12.08					s 6.05
		s12.09					s 6.07
		s12.10			4.12		s 6.09
		12.15	1.50				6.14
					4.16		
					4.18		
A. M.	A. M.	P. M.	P. M.	P. M.	P. M.	P. M.	P. M.
DAILY	DAILY	Daily except Sat. & Sun.	Saturday	DAILY	DAILY	DAILY	Daily except Sat. & Sun.

No. 71 will use freight track from 74th St. to Oakdale, unless otherwise instructed.

## SOUTHWARD

				FII	RST CLA	SS
	The fact to	icago	113	415	451	417
Telephone Stations	STATIONS	Distance from Chicago	Wab. 113 Pass.	Santa Fe 15 Pass.	Erie 2 Pass.	Santa Fe 17 Pass.
T elepho		Distan	Daily ex. Sat. & Sun.	DAILY	DAILY	DAILY
)-N			P. M. 5-30	P. M. 6.00	P. M. 6-05	P. M. 6-30
)-N	A. T. & S. F. JCT	1.3	5.35	6.05	6.10	6.35
-N	40TH ST	3.7	5.38		6.13	
N	47TH ST	4.6	s 5.39		6.14	
	49TH ST. (G. T. Conn.)	4.9				
	FFTH 6T	5.6				
-N	FORD ST. (59th ST.)	6.0	5.42		6-17	
-N	ENGLEWOOD	6.6	s 5.44		s 6.19	
-N	74thST.JCT. (Hamilton Pk.)	7.9	5.47		6.21	
	AUBURN PARK (79TH ST.)	8.7				
N		9.0			6.23	
-N		12.3			6.28	
	.SO. DEERING (112th St.).	15.0			6.32	
-N	MAIN LINE BRIDGE	16.5			6.34	
	FORD CROSSOVER	17.6			6.35	
N	BURNHAM	18.2			6.36	
-N		19.8			6.38	
-N	HAMMOND	20.8				
-N		23.3				
	OAKDALE	10.1				
	EUCLID PARK	11.0			TOTAL	
	FERNWOOD	11.7				
	NORTH ROSELAND	12.2				
	ROSELAND	12.7				
	SSHELDON PARK	13.2				
	KENSINGTON	13 6				
0	DOLTON	16.6				
N	DOLTON JCT	16.8				
-N	ArYARD CENTER	18.0				
			P. M.	P. M.	P. M.	P. M.
_	Figures between Stations show Distances	_	Daily except Sat. & Sun	DAILY	DAILY	DAILY

			FIF	RST CLA	SS			
1	207	463	409	95	215	407		
C. & E. I. 1 Pass.	G. T. W. 8 Pass.	Erie 8 Pass.	Santa Fe 9 Pass.	C. & E. I. 95 Pass.	G. T. W. 14 Pass.	Santa Fe 7 Pass.	1/-	
DAILY	DAILY	DAILY	DAILY	DAILY	DAILY	DAILY		
P. M 7-25	P. M. 8-10	P M 9.30	P. M. 10.00	P. M 10-30	P.M 10-40	P. M 11-55		
7.30	8.15	9.35	10.05	10.35	10.45	12.01		
7.33	8.19	9.38		10.38	10.49			
7.34	8.20	9.39		10.39	10.50			
	8.21				10.51			
7.37		9.42		10.42				
7.39		8 9.44		s10.44				
7.41		9.46		10.46		979		
7.43		9.48		10.48		-		
		9.53				-11		
		9.55			11		11 12/11	
		9.59				NO DE		
		10.00				Maria Tauri		
		10.01				20.00	777	
		10.03				Di		
7-46				10.51		Autor		
						0		
							-	-
						HIRLY'S III	CHARA	
7.51				10.56	-			-
7.55				11.00		750.10		
7.58				11.03		H THE		
P. M.	P. M.	P. M.	P. M.	P. M.	P. M.	A. M.		
DAILY	DAILY	DAILY	DAILY	DAILY	DAILY	DAILY		

## NORTHWARD

				FIF	RST CLA	SS
	1911 11	ilcago	454	408	94	206
I elephone Smittons	STATIONS	ce from Chicago	Erie 7 Pass.	Santa Fe 8 Pasa,	C. & E. I. 94 Pass.	G. T. W. 5 Pass.
ndata :		Distance	Daily except Monday	DAILY	DAILY	DAILY
N	ArCHIÇAGO		A. M. 1.15	A. M. 3.30	A. M. 4.45	A. M. 6.00
N	A. T. & S. F. JCT	1.3	1.10	3.25	4.40	5.55
N	40TH ST	3.7	1.06		4.36	5.49
ī	47TH ST	4.6	1.04		4.35	5.47
	49TH ST. (G. T. Conn.)	4.9				5.46
	55TH ST	5.6				
N		6.0	1.01		4.31	
N	ENGLEWOOD	6.6	f 1.00		s 4.30	
N	74th ST. JCT. (Hamilton Pk.)	7.9	12.58		4.28	
	AUBURN PARK (79TH ST.)	8.7				
N		9.0	12.56		4.26	
N		12.3	12.52			
	.50. DEERING (112th St.).	15.0	12.49			
V		16.5	12.47			
	FORD CROSSOVER	17.6	12.45			
N		18.2	12.44			
N		19.8	12.42			
N	HAMMOND	20.8				
N	LvSO, HAMMOND	23.3				
	OAKDALE	10.1			4.24	
	EUCLID PARK	11.0				
	FERNWOOD	11.7				
	NORTH ROSELAND	12.2				
	ROSELAND	12.7				
	5 SHELDON PARK	13.2				
	KENSINGTON	13.6			4.19	
1	DOLTON	16.6				
N	DOLTON JCT	16.8			4.15	
-	LvYARD CENTER	18.0	100		4.13	
			A. M.	A. M.	A. M.	A. M.
_	Figures between Stations show Distances		Daily except Monday	DAILY	DAILY	DAILY

The following signs indicate:—s Regular Stop; f Flag Stop; D Day; N Night.

420	66	112	216	452	416	54	72
Santa Fe 20 Pass.	C. & W. I. Pass.	Wab. 112 Pass.	G. T. W. 15 Pass.	Erie 1 Pass.	Santa Fe 18 Pass.	C. & E. I. 54 Pass.	C. & W. I. Pass.
DAILY	Daily except Sunday	Daily except Sat. & Sun.	DAILY	DAILY	DAILY	DAILY	Daily except Sat. & Sun.
A.M. 7·15	A.M. 7.35	A. M 8.00	A. M. 8-20	A.M. 8.35	A.M. 9.00	A.M. 9.45	P. M. 12.55
7.10	7.30	7.55	8.15	8.30	8.55	9.40	12.51
	7.25	7.49	8.10	8.26		9.36	12.49
	s 7.24	s 7.48	8.08	8.25		9.35	s12.46
			8.06				
	s 7.21						s12.41
		7.44		8.21		9.31	
	s 7.17	s 7.43		s 8.20		s 9.30	s12.38
	s 7.13	7.40		8.18		9.28	s12.35
	8 7.11						s12.34
	7.10			8.16		9.26	12.33
				8.12			- C 10 E
				8.09			51246
				8.07			
				8.05		THE REAL PROPERTY.	
				8.04		-	NC.W
				8.02			
							101
						100	
	s 7.07					9.24	s12.31
	s 7.05						s12.29
	s 7.03					1	s12.28
	s 7.01						s12.27
	8 6.59					-	s12.26
	s 6.57						s12.25
	s 6.55					9.19	s12.24
	6.50						12.20
						9.15	
						9.13	-
A. M.	A. M.	A. M.	A. M.	A. M.	A. M.	A. M.	P. M.
DAILY	Daily except Sunday	Daily except Sat. & Sun.	DAILY	DAILY	DAILY	DAILY	Daily except Sat. & Sun.

		900		FI	RST CLA	ASS	
2	bis a	Chicago	418	402	124	306	
Telephone Stations	STATIONS	from	Santa Fe 18 Pass.	Santa Fe 2 Pass.	Wab. 124 Pass.	Monon 6 Pass.	
Teleph	- x* -p	Distance	DAILY	DAILY	DAILY	DAILY	-
D-N	ArCHIÇAGO		P. M. 1.30	P. M. 2.00	P. M. 2.45	P. M. 4-15	
D-N		1.3	1.25	1.55	2.40	4.10	
D-N		3.7			2.36	4.06	
D-N		4.6			2.35	4.05	
		4.9					
	55TH ST	5.6					
D-N	FORD ST. (59th ST.)	6.0			2.30	4.01	
D-N	ENGLEWOOD	6.6			s 2.28	s 4.00	
D-N	74th ST. JCT. (Hamilton Pk.)	7.9	and.		2.25	3.58	
	AUBURN PARK (79TH ST.)	8.7					
D-N	81ST ST	9.0	L S			3.56	
D-N		12.3				3.52	
	.50. DEERING (112th St.).	15.0				3.49	
D-N		16.5				3.47	
	FORD CROSSOVER	17.6	10 11			3.45	
D-N		18.2				3.44	
D-N		19.8	COLUMN TO			3.42	
D-N	HAMMOND	20.8				s 3.35	
D-N		23.3				3.29	
	OAKDALE	10.1					
	EUCLID PARK	11.0				80.00	
	FERNWOOD	11.7					
	ROSELAND	12.2				11111111	
	ROSELAND	12.7					
	SSHELDON PARK	13.2					
	KENSINGTON	13.6					
D	DOLTON	16.6					
D-N	DOLTON JCT	16.8					
D-N	LvYARD CENTER	18.0					_
			P. M.	P. M.	P. M.	P. M.	n I
	Figures between Stations show Distances		DAILY	DAILY	DAILY	DAILY	

		714	FIF	ST CLA	SS		
456	424	218	92	412	110	450	
Erie 5 Pass.	Santa Fe 124 Pass.	G. T. W. 17 Pass.	C. & E. I. 92 Pass.	Santa Fe 12 Pass.	Wab. 110 Pass.	Erie 9 Pass.	Ally b
DAILY	DAILY	DAILY	DAILY	DAILY	DAILY	Sunday	
P. M. 4-20	P. M. 5-30	P. M. 7-10	P. M. 7-50	P. M. 8.00	P. M. 9-15	P. M. 11.59	
4.15	5.25	7.05	7.45	7.55	9.10	11.54	
4.11		7.00	7.41	11 11 11	9.05	11.50	
4.10		6.58	7.40		9.04	11.48	
		6.56					
4.06			7.36		9.01	11-45	
4.05			8 7.35			111.44	
4.03			7.33		8.57	11-42	
4.01			7-31			11.40	
3.57						11.36	
3.54						11.33	
3.52						11.31	
3.50			18			11.29	
3.49						11.28	
3.47						11.26	
0000	100		7.29			17.01	
			7.25				
			7.21			-	-
			7.18				
P. M.	P. M.	P. M.	P. M.	Р. М.	Р. М.	P. M.	
DAILY	DAILY	DAILY	DAILY	DAILY	DAILY	Sunday	FF F3

Book of Rules dated June 1, 1961, will govern in all cases except when they conflict with the following.

## SPECIAL INSTRUCTIONS

Supplements to this time table may be issued to cover changes in schedules and additional trains.

1—The tracks are designated by numbers commencing with No. 1 for the most easterly and continuing west, except that at 87th Street Nos. 1 and 2 tracks crossover Nos. 3 and 4 tracks and continue south on the west side to Pullman Junction. and where otherwise designated in these rules. No 3 track located east of No. 1 track between 81st Street and 49th Street.

## CURRENT OF TRAFFIC IS AS FOLLOWS:

MAIN LINE BETWEEN	TRACK	No. 2 TRACK	No. 3 TRACK	TRACK	TRACK
State Line and Pullman Junction	Northward	Southward			
Pullman Junction and 80th-81st Street Jet	Northward	Southward	Northward	Southward	
81st Street and 49th Street	Northward	Southward			
49th Street and 14th Street Sig. Bridge	Northward	Southward			
80th Street and Ford Street				Northward	Southward
46th Street and 22nd Street			Northward	Southward	
DOLTON BRANCH BETWEEN					
81st Street and Yard Center	Northward	Southward			
80th Street and Oakdale			Northward	Southward	

# FOLLOWING TRACKS EQUIPPED WITH AUTOMATIC BLOCK SIGNALS:

MAIN LINE BETWEEN	No. 1 TRACK	TRACK	No. 3 TRACK	No. 4 TRACK
State Line and Pullman Junction	Northward	Southward		
Pullman Junction and 80th-81st Street Jct			Northward	Southward
81st Street and 49th Street	Northward	Southward		
49th Street and 14th Street Sig. Bridge	Northward	Southward		
DOLTON BRANCH BETWEEN				
81st Street and Yard Center	Northward	Southward		

Rules 251 to 256 inclusive, 281 to 292 inclusive and 505 to 519 inclusive are in effect.

Signals used to give indication under these rules are—INTER-LOCKING, TRAIN ORDER and HAND SIGNALS where switch-tenders are located.

# FOLLOWING TRACKS EQUIPPED WITH BLOCK SIGNALS IN BOTH DIRECTIONS:

MAIN LINE BETWEEN		Cal Tra	
Pullman Junction and 80th-81st Street Jct	No. 1 TRACK	No. 2 TRACK	
81st Street and 47th Street			No. 3 TRACK

Rules 261 to 264 inclusive, 281 to 292 inclusive and 505 to 519 inclusive are in effect.

# FOLLOWING TRACKS NOT EQUIPPED WITH AUTOMATIC BLOCK SIGNALS:

MAIN LINE  BETWEEN  80th Street and Ford Street	No. 3 TRACK	No. 4 TRACK Northward	No. 5 TRACK Southward
DOLTON BRANCH BETWEEN  80th Street and Oakdale	Northward	Southward	

Rules 251 to 256 inclusive, 281 to 292 inclusive are in effect, and except as otherwise provided, movements not arranged by timetable or train orders may be made in the direction of current of traffic as per Rule 97, at reduced speed not exceeding 30 MPH.

SIGNALS used to give indication under these rules are—INTER-LOCKING, and HAND SIGNALS where switchtenders are located.

1-A—Between State Line and South Hammond is single track, known as MONON track. This track is within MONON YARD LIMITS, under jurisdiction of C&WI train dispatcher and is governed by C&WI R.R. time-table and Operating Rules.

The siding at South Hammond to which the schedule of trains apply under time-table and train orders, is from the crossover switch at SOUTH END OF PASSING TRACK to crossover switch at MIDDLE CONNECTION opposite bracket pole 22.8 and 22.9. All single track rules are in effect.

All Northward scheduled trains departing from South Hammond will receive a clearance form 902 from C&WI dispatcher as authority for movements.

## 1-B-YARD TRACKS

TRACK	BETWEEN	ASSIGNED DIRECTION	CONTROLLED	NOTE
No. 3	22nd Street and 16th Street	Northward	Interlocking Signals	1-2-3
No. 4	16th Street and 22nd Street	Southward	Interlocking Signals	1-2-3
No. 6	22nd Street and 42nd Street	None	Interlocking Signals	1-2-3-
No. 6	Ford Street and 80th Street	None	Interlocking Signals	1-2-3
East Lead	14th Street and 16th Street	None	Interlocking Signals	1-2-3
West Lead	14th Street and 16th Street	None	Interlocking Signals	1-2-3
No. 3	126th Street and Fernwood	None		1-2-5

Note 1-Movements governed by TIMETABLE RULE 1-O.

Note 2-Rules 99 and 201 to 223 inclusive do not apply.

Note 3-Rules 252 and 281 to 292 inclusive will apply.

Note 4—All trains, engines and Track Motor Cars entering C&EI yard, Canal Street Team Track at 31st Street or Canal Street Team Track at 23rd Street MUST report when in clear of track 6 to the Levermen at 40th Street or 21st Street. No train, engine or Track Motor Car will enter onto or foul track 6 at connection to C&EI Yard, Canal Street Team Track at 31st Street or Canal Street Team Track at 23rd Street without first securing permission from leverman at 40th Street or 21st Street. Telephones have been installed at the above locations for this purpose.

Note 5—On No. 3 track automatic crossing gates are operated by short circuit through the street. Trains using this track in either direction must come to a stop at stop board located to the right of the track near the crossing and will not proceed over street crossing until gates lower to horizontal position.

## 1-C—SIDINGS OF ASSIGNED DIRECTION

TRACK	BETWEEN	ASSIGNED DIRECTION	CONTROLLED	NOTE
	State Line and Burnham	Northward	Interlocking Signals	1
	Burnham and State Line	Southward	Interlocking Signals	1
***********	110th Street and Pullman Jet.	Northward		2

## Note 1-Rules 99-105-252-255 and 281 to 292 inclusive apply.

Interlocking signal indication governing movement to siding will be authority to use siding in reverse direction. Before entering siding from connections to Wabash, C&O, and CSS&SB R.R.Co. tracks trains must stop in clear and secure permission from Leverman Burnham Tower.

## Note 2-Rules 99-105-252-255 apply.

This track must not be used in either direction without permission from train dispatcher. Crews will handle switches at 110th St., leaving same lined and locked for track No. 1.

## HAND OPERATED SWITCHES EQUIPPED WITH ELECTRIC LOCK

The following switches are equipped with electric lock; Permission to unlock must be obtained from leverman before switch lock is removed from keeper. Instructions are posted on inside of telephone box.

LOCATION	SWITCH	CONTROLLED BY
13th Street	Crossover from WEST lead to MONON lead	Leverman Roosevelt Road
47th Street	From No. 1 track to Milk Spur	Leverman 47th St.
65th Street	From No. 3 track to Standard Mtl.	Leverman 74th St.
71st Street	From No. 3 track to Howes Lbr. Co.	Leverman 74th St.
78th Street	From No. 3 track to Cook Indstl.	Leverman 74th St.
115th Street	From No. 2 track to C.S.L. Yard	Leverman Main-Line Bridge

#### SPRING SWITCHES

LOCATION	NORMAL POSITION	ROUTE FOR WHICH SPRUNG
51st Street	East fuel track	Inbound Engine lead

This switch is equipped with standard spring switch indicator.

All instructions pertaining to spring switches are in effect.

## 1-D-AT ROOSEVELT ROAD.

Between DEARBORN STATION and 14th STREET SIGNAL BRIDGE. All tracks are included in TAYLOR STREET YARD, governed by TIMETABLE RULE 1-O, and are under the jurisdiction of the YARDMASTER located in Interlocking station ROOSEVELT ROAD.

Between ROOSEVELT ROAD (12th Street) and 14th Street Signal bridge, trains and engines will be governed by STANDARD INTER-LOCKING SIGNALS.

Northward trains and engines must not pass NORTH LINE OF ROOSEVELT ROAD VIADUCT until proper hand signal is given by SWITCHTENDER on ground.

Southward trains and engines may use NORTHWARD No. 1 track from ROOSEVELT ROAD to crossover to EAST LEAD near 15th STREET or to crossover to SOUTHWARD TRACK No. 2 or SOUTHWARD TRACK No. 4 at 17th Street on SIGNAL INDICATION.

#### 1-F-IN 18TH STREET YARD.

No. 2 track is a southward running track and No. 7 is a northward running track, these tracks MUST NOT be used for storage purposes.

## 1-G-AT 80TH STREET.

Junction of C&WI main line and Dolton Branch tracks, Nos. 3 and 4, BELT RY. of CHICAGO and connection with MAIN LINE tracks 1 and 2 and DOLTON BRANCH tracks 1 and 2, Switches are handled by switchtenders.

All trains must come to a stop at the stop-boards and will then proceed only on proper hand signals from the switchtender.

## 1-H-AT PULLMAN JUNCTION

All northward trains must come to a full stop at stop boards located 160 feet south of NKP CROSSING and all southward trains must come to a full stop at SEMAPHORE SIGNALS, and proceed only on clear signal indication.

For all irregular movements a train must not proceed until route is completed and proper hand signal is given by switchtender as directed by the C&WI OPERATOR.

Trains moving from C.R.I.&P. or PULLMAN R.R. to C. & W. I. must secure permission from C&WI OPERATOR before opening switch at either end of crossover and must lock switches after move is completed.

## PULLMAN JUNCTION—C.R.I.&P. CROSSING.

Trains will be governed by a semaphore and gate combined, DI-AGONAL position of semaphore and open position of gate indicates proceed for trains on the C&WI tracks, any other position of the target and gate is a stop signal for C&WI trains.

## PULLMAN JUNCTION—NICKEL PLATE CROSSING.

Trains will be governed by a SEMAPHORE or TILTING TARGET located at the crossing, a VERTICAL or STRAIGHT UP-AND-DOWN position of this target indicates clear for C&WI trains in either direction, any other position of the target is a stop signal for C&WI trains.

The semaphore signal governing northward movements to C&WI tracks Nos. 1 and 2, and BELT track No. 1 located to the right of C&WI track No. 1 about 25 feet north of C.R.I.&P.R.R. crossing has two arms.

TOP ARM governs movement to C&WI track No. 1.

LOWER ARM governs movements to C&WI track No. 2 and BELT track No. 1.

Trains from NKP to C&WI or BELT must not foul C.R.I.&P. crossing until proceed signal is displayed at crossing and proper hand signal received from switchtender located north of this crossing. Trains enroute to NKP must not foul CRI&P crossing until YELLOW color light signal is displayed at C&WI-NKP connection.

A CLEAR SEMAPHORE indication or a HAND SIGNAL does not give any train the right to proceed over the CRI&P or NKP crossing until complete STOP has been made.

## 1-J-AT SOUTH DEERING (112th STREET).

This interlocker is operated from MAIN LINE BRIDGE by remote control.

Crews desiring to crossover or enter main tracks will, on arrival call LEVERMAN at MAIN LINE BRIDGE informing him of moves to be made. Telephones for this purpose are located, near HOME SIGNAL on BELT RAILWAY DISTRICT track and at switch to CSL yard near 115th Street. These boxes are equipped with switch lock and must be locked after using.

## 1-K-AT FORD CROSSOVER.

At the connection with the FORD plant or the SOUTHSHORE YARD just south of 130th Street, and also the HEGEWISCH team track located near 135th Street, no train or engine will enter onto main tracks or crossover from one main track to another main track without permission of the Train Dispatcher. When ready to make such moves the Conductor will call leverman at the MAIN LINE BRIDGE advising him what move is to be made and leverman will secure permission from the train dispatcher for train to occupy the main track or use the crossover. Such moves must be made under flag protection and the leverman advised when such moves have been completed and main track is cleared. Leverman will so inform the train dispatcher.

Telephone for communication with leverman at MAIN LINE BRIDGE is located in booth to right of No. 2 track near Ford Switch.

## 1-M-AT YARD CENTER.

All trains except first class must be cleared with clearance FORM 902 before entering onto C&WI MAIN TRACKS, as required by Rule 211.

Northward train order signal arm is removed. When train orders are to be delivered to a northward train, a RED or YELLOW flag or light will be displayed on the mast which carries the southward train order signal. When approach indication is displayed by northward home signal at YARD CENTER interlocking, enginemen will reduce speed sufficiently to permit picking up train order hoop at YARD CENTER telegraph office.

## 1-N-YARD LIMITS.

## YARD LIMIT BOARDS ARE LOCATED.

For ERIE HAMMOND YARD, just north of State Line.

For MONON SOUTH HAMMOND YARD just north of State Line. For C&EI YARD CENTER, YARD, 50 feet south of 134th street.

Within Yard Limits the main tracks may be used protecting against FIRST CLASS trains, protection against extra trains and engines is not required.

Within YARD LIMITS extra trains and engines must move as

prescribed in timetable Rule 1-0.

Approach or proceed automatic block signal indications, or a hand, flag or lamp proceed signal within YARD LIMITS, does not modify the requirements of Rule 93.

On two or more tracks, a train or engine must not be moved against the current of traffic within YARD LIMITS until provisions have been

made to protect such movements.

Before using the main track within YARD LIMITS, it must be known that all overdue first class trains have arrived or left.

#### 1-O-YARD RULE.

Trains and Engines, will run at a speed consistent with conditions, prepared to stop short of a train, engine, car, switch improperly lined or any other obstruction.

In case of accident responsibility rests with approaching train.

Where HAND signals are necessary, train and engine crews must know that signals are intended for them, and that switches are properly lined.

## 2—APPROACHING STATIONS.

Trains must use caution in passing a train entraining or detraining passengers at a station; and must not pass between the train and station at which passengers are being entrained or detrained.

Trains must approach stations where a PASSENGER TRAIN MAY BE EXPECTED to be STANDING or APPROACHING under such control as to avoid passing it while at the station.

When passenger trains approach a station from opposite directions simultaneously the SOUTHWARD train shall have preference.

All trains must use caution approaching and passing 63rd Street (Englewood Station) as there may be persons walking to and from Stations and platforms.

## 3—CLEARANCE FORM.

All trains departing from Dearborn Station will receive a clearance FORM 902 from the C&WI dispatcher as authority for movement.

(a) -Schedule.

First class trains of tenant lines, on arrival at junction points will use the tracks with the current of traffic and assume the schedule on C&WI timetable when such schedule corresponds in number, class, and direction with the time-table of such tenant line.

(b) -Sections.

When C&EI-WABASH-ERIE-GRAND TRUNK—or AT&SF first class trains are run in sections, the train orders issued by these companies authorizing display of signals will be authority to display signals over C&WI tracks unless otherwise ordered by the C&WI train dispatcher.

(c)-Regulation Traffic.

In regulating the passage of trains over the tracks, on a question of passage or crossing the trains of the several companies shall have precedence according to class, in the following order—First C&EI—Second—WABASH (Decatur Division) Third G.T.W. Fourth ERIE—Fifth MONON Sixth WABASH (Detroit Division) Seventh AT&SF, Eighth C&WI. This rule must not be understood as giving any superiority to a train of inferior class over a train of superior class, but is only to affect trains of the same class in regard to each other.

#### 4-PILOTS

Officers of other companies responsible for handling train and engine crews will know that such crews have been properly qualified before assigning them to operate over C&WI tracks, otherwise they will request a pilot. Pilots are to be ordered from C&WI train dispatcher.

Foreign or tenant line trains on arrival at their yards or junctions must clear C&WI tracks promptly and must not be held out of yards waiting for track room. Switching on or from main tracks is POSITIVELY forbidden unless permission is obtained from dispatcher.

#### 5—AUTHORIZATIONS.

Operators or Switchtenders must obtain permission from the C&WI train dispatcher before permitting a train or track motor car to enter onto C&WI tracks, except that schedule trains may be cleared without such authority when communication with train dispatcher is interrupted.

## 6—OBSTRUCTIONS.

In case of track being obstructed from any cause, making it necessary to move trains around the obstruction, trainmen, must familiarize themselves with the situation and where possible advise train dispatcher promptly and ask for instructions. When unable to reach the train dispatcher promptly they should arrange to flag their train around the obstruction, protecting it properly by flag.

When from any cause a freight train is unable to clear the main track promptly for a passenger train, where possible they must immediately advise the train dispatcher and ask for information, when unable to contact the train dispatcher, the conductor and engineer must arrange to run the passenger train around, protecting it properly by flag.

## 7—ACCIDENTS.

In case of accident the Conductor, will at once report to the Superintendent by wire from the nearest telephone office, giving cause of accident, extent of damage, what tracks are blocked if any, and what assistance is required; if the steam derrick is needed, on what track the derrick should be sent to work to the best advantage, also

state if the track men are required. A regular report on Form 618 must be filled out by the Conductor and Engineer, and forwarded to the Superintendent not later than the following day after the accident occurs.

#### 8-OBSERVANCE.

Conductors and Foremen of Engines must have some member of the crew on or near the rear of train when passing crossings and towers where Operators and Switchtenders are on duty, to be in a position to exchange signals with these employes when necessary. Operators, Levermen and Switchtenders must observe passing trains and note whether they are complete and in order; should there be any indication of conditions endangering the train, or any other train, they shall endeavor to signal some member of the crew, notify train dispatcher or take such measures for the protection of trains as may be practicable.

## 9-STANDARD CLOCKS ARE LOCATED:

Telegraph Office-Dearborn Station.

49th Street Roundhouse.

Yard Offices-Taylor Street and 51st Street Coach Yard. South Hammond.

## 10-BULLETIN BOARDS ARE LOCATED AT:

Telegraph Office-Dearborn Station.

Yard Office-Taylor Street and 51st Street Coach Yard.

49th Street Roundhouse.

Erle Yard Office-51st Street.

Yard Center-C&EI.

State Line.

South Hammond-MONON.

## 11-REGISTER BOOKS ARE LOCATED AT:

Telegraph Office-Dearborn Station.

Yard Center for C&EI.

South Hammond for MONON.

Conductor will be particular to give the exact number of cars in their trains counting the caboose as one car.

## 12-TRAIN ORDER SIGNALS ARE LOCATED AT:

Pullman Junction.

State Line.

South Hammond-MONON.

81st Street, Southward Only

Yard Center-C&EI.

## 13—CROSSING GATES ARE ESTABLISHED AT THE FOLLOW-ING STREET CROSSINGS:

All trains must approach the crossing prepared to stop before passing over if the gates are not down unless given a clear hand signal from the crossing watchman. This rule applies to trains of every class. Conductors will report all delays caused by not getting proper signals at crossings.

All trains must approach street crossings at grade within municipalities with caution, and where view is obstructed from any cause, with train under control.

Engines must not be backed nor cars pushed over grade crossings in switching movements within municipalities unless a member of the crew operating such engine or train either rides the tender or foremost car in a position to observe all danger and to assist in stopping train if necessary or actually flags the crossing if crossing is unprotected by flagman.

In cases of accident between vehicle and train in which the matter of flashing lights and automatic gates is involved, it must be thoroly understood that in case flashers and gates cut out and cease to operate after train has passed over the crossing, in order to show that flashers and gates are working, the train will back up over the crossing and let the flashers and gates operate and get witnesses of the fact that they are operating and make necessary reports of such transactions.

MAIN LINE LOCATIONS	Automatic Gates	Automatic Manual Gates	Manual	Automatic Flashers	Automatic Bells	Manual Flashers	Protected By Std. Crossbuck Only
14th Street			X			X	
112th Street			X	X	x		
114th Street							X
117th Street							x
130th Street			X		x		
134th Street			X				
135th Street				x	x		
136th Street				X	x		
BURNHAM AVENUE			x				
DOLTON BRANCH LOCATIONS							
	X	-		x			-
95th Street		-	_				x
97th Street 101st Street		-		x			_ A
	x	-		X	X		-
103rd Street	X	_		X	X		-
107th Street							
109th Street	-	-		X	X		-
111th Street	X			X	X		-
113th Street		X		X	X		
PRINCETON AVENUE		X		X	X		
WENTWORTH AVENUE		X		X	X		
PERRY AVENUE		X		X	X		
115th Street		X		X	X		
LAFAYETTE AVENUE		X		X	x		
STATE STREET		X		x	x		
130th Street	X			X	X		
133rd Street							X
134th Street		1	y				X
138th Street						x	
LINCOLN AVENUE			X			X	

## 14—SPEED RESTRICTIONS—

LIMITS BETWEEN  Maximum permissible speed against current of traffic 30 M.P.H.	Tracks Equipped With Automatic Block Signals	Tracks Not Equipped With Automatic Block Signals	Diverging Routes
14th St. and 22nd St	20 MPH	Reduced Speed	
THRU 16th St. Interlocking Limits			- 10 MPH
THRU 21st St. Interlocking Limits			10 MPH
FROM 21st St. Interlocking Limits to NORTH Limits 40th St. Interlocking	60 MPH	Reduced Speed	
THRU 40th St. Interlocking Limits	45 MPH	Reduced Speed	10 MPH
FROM SOUTH Limits 40th St. Interlocking and THRU 81st St. Interlocking Limits	45 MPH	Reduced Speed	
EXCEPTIONS:			
C&WI Southward thru 47th St. Interlocking Limits.	25 MPH		10 MPH
GTW Southward thru 47th St. Interlocking Limits	25 MPH		10 MPH
GTW Northward thru 47th St. Interlocking Limits.	15 MPH		10 MPH
THRU 74th St. Interlocking Limits	45 MPH	Reduced Speed	12 MPH
MAIN LINE			
THRU 81st St. Interlocking Limits	45 MPH		15 MPH
FROM 81st St. Interlocking Limits TO Pullman Junction.	60 MPH		
THRU 80th St. Limits	20 MPH	Reduced Speed	15 MPH
FROM 80th St. Limits TO Pullman Junction	60 MPH		
THRU Pullman Jet	30 MPH		12 MPH
FROM Pullman Jct. TO South Deering Interlocking Limits	60 MPH		
THRU South Deering Interlocking Limits	35 MPH		12 MPH
FROM South Deering Interlocking Limits TO Main Line Bridge Interlocking Limits	45 MPH		
THRU Main Line Bridge Interlocking Limits	20 MPH		
FROM Main Line Bridge Interlocking Limits TO Ford Crossover	50 MPH		
FROM Ford Crossover TO Burnham Interlocking Limits	60 MPH		
THRU Burnham Interlocking Limits	50 MPH		12 MPH
FROM Burnham Interlocking Limits TO State Line Interlocking Limits	50 MPH		
	40 MPH		15 MPH

LIMITS BETWEEN DOLTON BRANCH Maximum permissible speed against current of traffic 30 M.P.H. Maximum permissible speed for freight trains 40 M. P. H.	Tracks Equipped With Automatic Block Signals	Tracks Not Equipped With Automatic Block Signals	Diverging Routes
THRU 80th St. Limits	20 MPH	Reduced Speed	15 MPH
THRU 81st St. Interlocking Limits			15 MPH
FROM 81st St. Interlocking Limits TO Oakdale Interlocking Limits	55 MPH		
THRU Oakdale Interlocking Limits	35 MPH		20 MPH
FROM 80th St. Limits TO Oakdale Interlocking Limits		Reduced Speed	
FROM Oakdale Interlocking Limits TO Dolton River Bridge	60 MPH		
EXCEPTIONS: Roseland Curve	50 MPH		
OVER Dolton River Bridge	30 MPH		
FROM Dolton River Bridge and THRU Dolton Interlocking Limits			12 MPH

# 15—EMPLOYES ARE WARNED OF CLOSE CLEARANCE AS FOLLOWS:

All tracks in Dearborn Station train shed and Taylor Street Yard.

Roosevelt Subway (12th St.)

West Cantilever Crossing Flashers and Gate-14th St.

16th. St. Subway.

18th. St. Viaduct and Yard Tracks.

West Leg Penna Signal Bridge, Track 1—Between 24th. St. and 24th. Place.

Signal Bridges-24th., 28th. and 33rd. Streets.

Automobile Platform—23rd. St. and Team Tracks, Canal Street. Yard—23rd. St. to 31st. St. Gantry crane tracks 46, 47 and 48 in Canal St.

Crane must be stationed at North end while switching Crane Tracks.

West Leg Penna Signal Bridge-track 1-32nd. St.

Signal Bridges at 38th., 40th. and 42nd. Sts. side clearance.

Bridge Girders all streets, 40th. St. to 71st. St. side clearances.

West leg 49th. St. Signal Bridge.

West leg Penna Signal Bridge 150 feet north Root St.

51st. St. Coach Yard (side clearances)

Englewood Freight House and Team Tracks.

C.R.I.&P. overhead crossing 79th. St.

Overhead clearances 87th. St.

Chatham Coal Co.-109th. St. (Overhead clearances) Dolton Branch.

Sanitary District tracks, 126th. St., Dolton Branch. All industry tracks at Warehouses and Coal Bins.

On account of the limited side clearances of Girders, Bridges, and other structures at various points along the C&WI tracks, all train and engine men are warned not to hang on side of engine or cars. Special attention is called to girder bridges in Englewood team yard and steel columns and platforms in Taylor Street Yard, Dearborn Station.

Train and Enginemen must not ride on top or hang on side of cars or Engines while passing above points, and when switching industries or tracks in Taylor Street Yard must use extreme caution at all times.

## 5—PERMISSIBLE CLEARANCE LIMITS FOR MOVEMENTS OVER THE C.&W.I.R.R.

Distance above

Width of car

				top of rail	or load
(1)	Dearborn Street.	Station	to 20th		
				Below 3 inches	7'0"
				3" to 1'3"	9'0"
				1'3" to 2'0"	10'0"
				2'0" to 15'9"	10'6"

Extreme height not to exceed 15'9". Extreme width not to exceed 10'6".

## (2) 20th Street to 75th Street.

Below 3	inches	7'0"
3" to	1'3"	9'0"
1'3" to	2'0"	10'0"
2'0" to	5'6"	10'6"
5'6" to	20'9"	11'6"

Extreme height not to exceed 20'9". Extreme width not to exceed 11'6"

## (3) 75th Street to Pullman Junction or Oakdale

Below 3 inches	7'0"
3" to 2'0"	10'0"
2'0" to 17'0"	11'6"

Extreme height not to exceed 17'0"—Extreme width not to exceed 11'6".

## (4) Pullman Junction to State Line, Oakdale to Dolton.

Below 3 inches	7'0"
3" to 2'0"	10'0"
2'0" to 18'0"	11'6"

Extreme height not to exceed 18'0". Extreme width not to exceed 11'6".

Cars and loads exceeding these dimensions must be approved prior to movement.

## 16-INCOMPLETE MOVEMENTS.

When a train or engine, having accepted a proceed signal, is delayed in starting, or stops after starting, the OPERATOR or SWITCH-TENDER must be notified promptly as to the cause and probable duration of the delay. Such train or engine must not again start without securing permission of the OPERATOR or SWITCHTENDER.

## 17—TELEPHONES FOR COMMUNICATION TO FOLLOWING IN-TERLOCKING STATIONS. CODE RINGS TO—

12th. St. 2 shorts.

15th. St. 3 shorts.

16th. St. 2 long 2 shorts.

21st. St. 1 long 2 shorts.

## Locations-

14th. St. ERIE crossingman's cabin.

14th. St. East side signal bridge WABASH lead.

15th. St. on retaining wall-just east of CLARK ST.

18th. St. on pole east of No. 1 track.

20th. St. on southward home signal track 2.

## Track Phones to 21st. St.

21st. St. power house.

On 22nd. St. Santa Fe inbound signal pole.

On 23rd. St. Automobile platform.

31st. St. pole south end Canal St. yard and first pole north tool house.

## Track Phones to 40th. St. Ring 1 long 3 shorts.

31st. St. pole south end Canal St. yard and first pole north tool house.

## FOLLOWING ARE AUTOMATIC TRACK PHONES.

On west end signal bridge 38th. St.

On post entrance to north "Y"

On signal pole 39th. St. north "Y"

On signal pole 40th. St. south "Y"

On post 41st. St. Wabash lead.

On west end signal bridge 42nd. St.

## 47th. St. Automatic Track Phones.

On signal mast 45th. St. track 6.

On west end signal bridge 46th. St.

On post 100 ft. north 47th St. Wabash lead.

On post to entrance 47th. St. milk spur.

On signal bridge 49th. St. East Side.

On west end signal bridge 49th. St.

On post outbound engine lead.

On signal pole on west lead.

On signal pole No. 3 track-northward home signal.

## Track Phones to 47th. St. Ring 3 long 3 short.

On post east side of Track No. 3 at 53rd. St.

## Track Phones to Ford Street. Ring 5 shorts.

North End 55th. St. viaduct.

## 17—TELEPHONES FOR COMMUNICATION TO FOLLOWING IN-TERLOCKING STATIONS. CODE RINGS TO—Concluded

## Track Phones To 74th. St. Ring 3 short 1 long.

On post east side track 3 at 65th. St.

On post east side track 3 at 71st. St.

On east end signal bridge 72nd. St.

On east end signal bridge 74th. St.

On post east side track 3 at 78th. St.

On post at signal Wabash connection.

## Track Phones To Main Line Bridge. Ring 1 long 1 short 1 long.

On pole at northward siding 110th. St.

On post near home signal on BRC district track.

On post CSL connection 115th St.

In concrete booth Ford Crossover.

On post east side of siding at 103rd St.

On post west side of No. 2 track at 119th St.

On post north side of No. 1 Track at facing point switch at 135th St.

## Burnham Tower. Ring 3 short 1 long.

On east side of C&O Yard Lead, south of Burnham Avenue Crossing.

## Track Phones To State Line. Ring 2 shorts.

On post east of C&O connection 200 feet south of southward home signal.

On post west side of southward siding at southbound home signal on Track 2.

## Track Phones To 81st Street Interlocking. Ring 2 short 2 long.

On post north of 95th St. east side of track.

On post west side of track 98th. St.

On post east side of track at south end of crossover 100th. St.

On west side of Fernwood station-103rd. St.

On pole 400 feet north of 109th. St. east side of track.

In box on west side of Roseland Station-111th St.

On pole 200 feet south of 115th. St. east side of track.

In cabin at 126th. St. east side of track.

In box south side of tool house 138th St.

In box east side of Dolton Station.

On Northward Home Signal 355 South of CRI&P Crossing

On Signal Case East Side of tracks 440 North of CRI&P Crossing.

On side of Signal Relay case west side of State Street Signal Bridge.

On side of Signal Relay case west side of Cottage Grove Avenue Signal Bridge.

Train and Enginemen held at a signal must contact leverman and inquire reason for being detained. When employes are thru with telephone, receiver must be properly hung on hook and door must be closed, if equipped with lock, lock same.

## 18-TRACK MOTOR CAR AND HY-RAIL TRUCK OPERATION:

Wherever the words "Track Motor Car" appear in this rule, they shall be construed as also applying to "Hy-Rail Trucks".

Employes using a track motor car must be fully conversant with and obey the Operating Rules and Special Instructions.

Operators of track motor cars must carry a copy of the current timetable and must know that the car is equipped with the necessary flagging equipment.

Track motor car must have an identification number.

A motor car Operator or a Flagman assigned to a track motor car, must secure permission from the Train Dispatcher thru leverman before entering on any track, stating the number of his track motor car. direction he is to move, points between which movement is to be made, and where he will clear the track, and must in all cases arrange to have the Train Dispatcher notified when car is clear of the track.

He must in all cases be governed by such instructions as the Train Dispatcher may issue.

Track motor cars must clear the track ten minutes before schedule trains are due.

Train Dispatcher must notify other than schedule trains, either by train order or message, when a track motor car ahead has not reached the next point of communication, otherwise the track motor car must be given the exclusive occupancy of the track.

When track motor cars use a Yard track, they will be governed by Yard rules.

Train Dispatcher must record all track motor car movements on train sheet in space provided for this purpose showing the originating and terminating points and track used.

Switchtenders at 80th Street and Levermen at all Interlocking Stations must record and report the movements of passing track motor cars at their stations.

On approaching an Interlocking plant track motor car must proceed only when proceed signal is displayed and must proceed at restricted speed throughout the interlocking limits, except at 80th Street, proper hand signal must be obtained before proceeding.

Movement against the current of traffic must not be made without permission of Train Dispatcher, and then only with exercise of every precaution to avoid meeting an opposing movement.

Track motor cars must stop at grade crossings and then proceed over crossing at restricted speed.

Operators of track motor cars or a Flagman assigned to a track motor car must understand that trains or other cars may be run on any track in either direction at any time and must at all times keep sharp look out and take such other measures as will insure safety.

Motor cars must display both day and night signals and track motor car Operators must afford protection as prescribed by Rule 99.

#### 19—SWITCHTENDERS.

Switchtenders are located at the following points—Taylor St., 80th St., and Pullman Jct.

It will be their duty to assist trainmen in turning switches and protecting their trains.

When giving hand signals they must guard against their being taken by other than train for which intended. They must stand on track the train is occupying, facing train when hand signal is given.

At all points where hand signals are required, switchtenders will use a YELLOW flag by day and YELLOW light by night for NORTHWARD trains, a GREEN flag by day and a GREEN light by night for SOUTHWARD trains.

At all points where switchtenders are located Train and Enginemen must know that signal is intended for them, switches properly lined and route is clear before proceeding. When necessary for trains to make an irregular movement, the Conductor or Engineer must have a thorough understanding with Switchtender or Dispatcher as to the intended movement, properly protecting themselves as the rules require.

## RULES OF OPERATING DEPARTMENT.

#### RULE 11-

A train, finding a fusee burning red on track it is using, will stop, extinguish fusee and proceed at restricted speed until a more favorable indication is observed expecting to find track occupied.

A train, finding a fusee burning red near track it is using, will stop and proceed at restricted speed expecting to find track occupied.

Lighted fusees must not be placed on or within 100 feet of public roads, street crossings, building, or any place which might result in injury to persons or damage to property.

## RULE 21-

Passenger Extras may display two white flags and in addition, two white lights by night, when the rules of the Operating Department of the Individual Railroad require it.

Note—Other train signals and markers of Railroads operating over the C&WI R.R. Co. tracks, are those prescribed in the rules of the Operating Department of the Individual Railroads.

## RULE 97-

Trains not scheduled on the C.&W.I. time-table will be designated as EXTRA trains and, except as provided in the special instructions, may use the tracks with the current of traffic, without running orders, and may run ahead of first class trains on signal indication.

#### RULE 105-

Unless otherwise provided, trains using a siding must proceed at Reduced speed.

A siding of an assigned direction must not be used in the reverse direction unless authorized by the employe in charge, or in an emergency under flag protection.

Unless otherwise provided, trains and engines must proceed at REDUCED SPEED unless the track upon which the movement is to be made is seen or known to be clear and switches properly lined.

## RULES OF THE OPERATING DEPARTMENT.

#### RULE 251-

On portions of the railroad, and on designated tracks so specified in the time-table, or by special instructions, trains or engines will run with reference to other trains in the same direction by fixed signals whose indications will supercede superiority of trains.

## RULE 251(a)-

Unless otherwise provided, a train authorized to run against the current of traffic must not be permitted to follow another train. The Operator will not clear signal until he has secured authority of the train dispatcher.

#### RULE 252-

The movement of trains will be supervised by the train dispatcher. Oral and message instructions issued by him must be complied with. When necessary to provide single track operation on double track, or to move trains against the current of traffic, or for operation of work trains, train order authority must be obtained.

## RULE 253-

The train dispatcher must be advised in advance of any known condition that will delay the train or prevent it from making usual speed.

## RULE 254-

A train or engine must not enter on nor foul the main track on any portion of the railroad where the movement is governed by these rules except by fixed signal indication, or until permission is received from the operator or train dispatcher. Permission must not be given by an operator without authority of train dispatcher, except that regular trains may be cleared without such authority when communication with the train dispatcher is interrupted.

## RULE 255-

When signal or permission has been given to a train it may proceed until instructed by signal indication or message to take the siding. Such instructions by message will when practicable, be given at a preceding station. When instructed by signal indication it may again enter the main track upon receiving the proper signal indication or on instructions from the train dispatcher.

Before a train or engine is permitted to run against the current of traffic outside interlocking limits, permission must be secured from the train dispatcher, who will issue necessary orders.

#### RULE 256-

When a train or engine is to be given exclusive occupancy of track, permission must be obtained from the train dispatcher specifying the clock time and the working limits. The train dispatcher will instruct the levermen to restore the signals to "stop" position and block the levers controlling signals governing movements into such limits, and blocks must not be removed until authorized by train dispatcher after train or engine has cleared such working limits.

Within such limits movements may be made in either direction without flag protection. Train and engine must be clear and reported clear of working limits before expiration of the time granted, and must not re-enter such limits without again obtaining permission from the train dispatcher.

## RULES GOVERNING OPPOSING AND FOLLOWING MOVEMENT OF TRAINS BY BLOCK SIGNALS.

## RULE 261-

Within defined limits on designated tracks, so specified on the timetable, or by special instructions, the movement of trains and engines will be governed by block signals whose indications will supersede the superiority of trains for both opposing and following movements on the same track.

Movement of trains and engines will be supervised by the Train Dispatcher who will issue instructions as may be required.

## RULE 262-

Unless authorized by signal indication, trains or engines must not enter or foul a main track at a hand operated switch without permission of Leverman who will first obtain authorization from Train Dispatcher including track and time limits per Rule 256.

If it becomes necessary to reverse the movement of a train or engine, except as provided in Rule 256, permission must be obtained from Leverman, who will first secure authorization from Train Dispatcher or the movement made at restricted speed under flag protection to the first point of communication.

## RULE 263-

The Train Dispatcher must be advised in advance of any known condition that will delay the train or prevent it from making usual speed.

#### RULE 264-

Except as affected by Rule 261 and Rule 262, all Operating Rules, Interlocking Rules and Automatic Block Signal Rules remain in effect.

## LOCATION OF AUTOMATIC BLOCK SIGNALS, ROOSEVELT ROAD TO 81st STREET.

	SOUTHWARD TRACKS		LOCATION	NORTHWARD TRACKS		
No. 3	No. 2	East Lead	DOUBLON.	No. 1	No. 3	East Lead
		1E	Roosevelt Road (250 ft. South)			
		3E	14th and Federal Street			2E
		5E	15th and Clark Street			
	5		18th and Grove Street			
			20th and Grove Street	6		
	9		24th and Stewart—Signal Bridge			
			28th and Stewart—Signal Bridge	10		
	15		33rd and Stewart—Signal Bridge	14		
			38th and Stewart—Signal Bridge	18		
	21		42nd and Stewart—Signal Bridge			
			47th Street	20		
047			49th Street			
	29		52nd Street			
			55th Street	28*	056	
	33		62nd and Wallace—Signal Bridge	32		
069	37		65th and Wallace—Signal Bridge	36	068	
			72nd and Wallace—Signal Bridge	44	076	
	41A 41B	}	74th and Wallace—Signal Bridge			
			80th and Wallace—Signal Bridge	52	088	

<sup>\*</sup>Denotes signal located to left of track governed.

# LOCATION OF AUTOMATIC BLOCK SIGNALS 81st STREET TO STATE LINE.

	UTHWA		MAIN LINE LOCATION		RTHWA	
No. 1	No. 2	No. 4		No. 1	No. 2	No. 3
		201F	81st Street			
093	091		82nd Street Signal Bridge			
		203F	86th Street and Stewart Avenue			
			87th Street and Stewart Avenue			202F
105	103	205F	State Street Signal Bridge	106	104	204F
115	113	207F	Cottage Grove Avenue Signal Bridge	114	112	206F
	213*		95th and Stony Island—Bracket Pole	214*		
	215*		99th and Cregier Ave.—Bracket Pole	216*		
	217		103rd Street Viaduct	218		
	219*		109th & Yates—Bracket Pole	220*		
	223		119th & Torrence Avenue	224		
	227		130th & Torrence Avenue			
			133rd & Muskegon Avenue	230		
			146th and Brainard Avenue	236		

<sup>\*</sup>Denotes signal located to left of track governed.

# LOCATION OF AUTOMATIC BLOCK SIGNALS 81ST STREET TO DOLTON.

SOUTHWARD			NORTHWARD TRACKS	
No. 4	No. 2	DOLTON BRANCH	No. 1	No. 3
	99	82nd and Vincennes Avenue—Signal Bridge		
	101	87th and Stewart Avenue—Bracket Pole	100A	
	105	94th and Stewart Avenue		
	D 02-5	100th Place and Stewart Avenue	D 02-4	
	109	105th and Stewart Avenue	108	
		110th and Stewart Avenue	110	
	111	109th and Stewart Avenue		
	112	114th and Yale Avenue	112	
		116th and Michigan Avenue—Bracket Pole	114	
	117	118th and Calumet Avenue		
		119th and South Park Avenue—Bracket Pole	116	
	110	124th and South Park Avenue—Bracket Pole	118*	
	191	130th and South Park Avenue—Bracket Pole	120*	
	100	134th and South Park Avenue		
	-	136th and South Park Avenue	122	

<sup>\*</sup>Denotes signal located to left of track governed.

## EXTRACT FROM ILLINOIS STATE LAW:

"All trains running on any railroad in this State when approaching a crossing with another railroad upon the same level, or when approaching a swing or drawbridge, in use as such, shall be brought to a full stop before reaching the same, and within eight hundred, (800) feet therefrom, and the Engineer or other person in charge of the engine attached to the train shall positively ascertain that the way is clear and that the train can safely resume its course before proceding to pass the bridge or crossing."

Every engineer or other person having charge of such engine, violating the provisions of the preceding section, shall be liable to a penalty of two hundred dollars for each offense to be recovered in an action of debt in the name of the people of the State Of Illinois, and the corporation on whose road such offense is committed shall be liable to a penalty of not exceeding two hundred dollars, to be recovered in like manner so recovered to be paid into the treasury of the county in which the offense occurs, but no recovery shall be had in any case for any offense committed more than sixty days prior to the commencement of the action. The provisions of this and of the preceding action shall extend to and govern all cases of neglect and failure to stop the train as required by law before passing any bridge or railroad crossing, whether occurring before or after the said provisions shall take effect, and no act or part of an act consistent with such operation and effect being given to this law shall in any way apply thereto".

NOTE—This law has been modified by a special enactment which provides that trains shall not be required to stop at grade crossing or drawbridge where interlocking signals are in operation and have been accepted by the State Commissioners.

## Chicago & Western Indiana R. R. Co.

Chicago, Illinois, October 28, 1962

## GENERAL ORDER NO. 14-1

## EFFECTIVE 12:01 A.M. SUNDAY OCTOBER 28, 1962

Timetable No. 14 in effect. It contains the necessary instructions issued in General Orders up to and including No. 13-17.

Each employe must examine each page of Timetable No. 14 to see that his copy is complete, pages properly lined up, and note changes.

This General Order is printed in Timetable No. 14 and will not be issued in sticker form.

M. SWISLOW, Superintendent.

## Chicago & Western Indiana R. R. Co.

Chicago, Illinois, October 29, 1962

## GENERAL ORDER NO. 14-2 MAIN LINE

## EFFECTIVE 12:01 P.M. MONDAY, OCTOBER 29, 1962

Traffic Control System, between 47th Street Interlocking and 81st Street Interlocking governing train movements on Track No. 3 in either direction in accordance with Rules 261 through 264 inclusive, IN SERVICE.

The location of Automatic Block Signals and Aspects displayed by signals between 81st Street and 47th Street on Track No. 3 changed as follows:

#### 49TH STREET

Southward Color Position Light signal No. 047 displaying Aspects in accordance with Rules 281F, 285F and 291C, IN SERVICE.

## 55TH STREET

Northward semaphore type signal No. 26, REMOVED.

Northward Color Position Light signal No. 056 displaying Aspects in accordance with Rule 281F, 285F and 291C, IN SERVICE.

#### 62ND AND WALLACE-SIGNAL BRIDGE

Northward semaphore type signal No. 30 and southward semaphore type signal No. 31, REMOVED.

#### 65TH AND WALLACE-SIGNAL BRIDGE

Northward semaphore type signal No. 34 and southward semaphore type signal No. 35—REMOVED.

Northward Color Position Light signal No. 068 and southward color position light signal No. 069 displaying Aspects in accordance with Rules 281F, 285F and 291C, IN SERVICE.

## 75TH AND WALLACE-SIGNAL BRIDGE

Northward semaphore type signal No. 42, REMOVED.

Northward color position light signal No. 076 displaying Aspects in accordance with Rules 281F, 285F and 291C, IN SERVICE.

Northward semaphore type signal No. 50, REMOVED.

Northward Color Position Light signal No. 088 displaying Aspects in accordance with Rules 281F, 285F and 291C, IN SERVICE.

The electric locks on track No. 3 at the following locations are controlled by the Operator at 74th Street Interlocking: IN SERVICE.

65th Street-Standard Material Switch.

71st Street-Howes Lumber Switch.

78th Street-Cook Industrial Switch.

M. SWISLOW, Superintendent.

## Chicago & Western Indiana R. R. Co.

Chicago, Illinois, October 28, 1962

## GENERAL ORDER NO. 14-3 DOLTON BRANCH

## EFFECTIVE 12:01 A.M. SUNDAY OCTOBER 28, 1962

Due to construction of South Route Expressway Grade Separation which commenced June 19, 1962, Main tracks Numbers 1 and 2, between 97th Street and 100th Street, also, Switch and Derail to C&EI Lead were relocated 140 feet West on a temporary run-around embankment. STILL IN SERVICE.

Temporary Slow Speed Signs as per Rule 40- (Speed Limit Signs). IN SERVICE.

M. SWISLOW, Superintendent.

Following signals will be used to notify crews of passing trains of defective conditions

HOT JOURNAL.....BY DAY

Nose held with one hand with other hand pointing toward track.

BY NIGHT-Stop signal.

BRAKES STICKING ..... BY DAY

Hands shoved in sliding motion out from body.

BY NIGHT-Stop signal

BROKEN WHEELS
DEFECTIVE TRUCK
DRAGGING BRAKE CONNECTION
LADING SHIFTED OVER SIDE OR END
OF CAR

Stop signal

SWINGING CAR DOOR OR ANY OTHER DANGEROUS CONDITION

## DIESEL LOCOMOTIVES

To provide greater advance warning to Maintenance of Way Forces DURING DAYLIGHT HOURS, Diesel locomotives must burn their headlights Dim during ordinary weather, and at full power when weather is dull and foggy.