


THE WESTERN PACIFIC RAILROAD CO.



WESTERN DIVISION



TIME 17 TABLE

In Effect 12:01 A. M. "Pacific" Time

SUNDAY, JUNE 19, 1932

This Time Table is for the exclusive use and guidance of the employes concerned. The Company reserves the right to vary from it at pleasure.

Always have the Book of Rules of the Transportation Department at hand for reference.

W. MASON,
Vice President and General Manager.

J. P. QUIGLEY,
Superintendent of Transportation.

T. E. COYLE,
Superintendent, Western Division.

J. H. LEARY,
Superintendent, Terminal Division.

Fuel, Water, Tons, Table, Scale, Wye, Bulletin, Register Station, Standard Clock.	SECOND CLASS				FIRST CLASS		Distance from San Francisco	Time Table No. 17 June 19, 1932		Distance from Stockton	FIRST CLASS		SECOND CLASS			Capacity of Sidings	
	46	82	92	62	4	2		3	1		91	61	81	Arrive Daily Ex. Sunday	Arrive Daily		Arrive Daily
	Fast Freight	Fast Freight	Local Freight	Fast Freight	Feather River Express	Scenic Limited		Feather River Express	Scenic Limited		Local Freight	Fast Freight	Fast Freight				
	Leave Daily	Leave Daily	Leave Daily Ex. Sunday	Leave Daily	Leave Daily	Leave Daily		Arrive Daily	Arrive Daily		Arrive Daily	Arrive Daily	Arrive Daily				
W. F. O.					7.00 PM	9.30 AM	0.0	DN	SAN FRANCISCO	93.8	8.00 AM	4.30 PM					
B. R. P.					7.35	10.00	3.5		WESTERN PACIFIC MOLE	90.3	s 7.30	s 4.00					
F. W. T. O. P. B. R. K.		10.00 PM	7.25 AM	5.45 AM	7.40	10.05	5.5	DN	OAKLAND YARD	88.8	7.25	3.55	2.15 PM	11.59 PM	2.00 AM		
		10.05	7.30	5.50	s 7.50	s 10.10	6.6		OAKLAND	87.2	s 7.20	s 3.50	2.05	11.49	1.50		
		10.17	7.43	6.00	f 8.00	10.20	9.6		FRUITVALE	84.2	f 7.00	3.32	1.45	11.30	1.35		
P.		10.27	8.00	6.14	8.08	10.28	13.5		ELMHURST	80.3	6.51	3.22	1.25	11.10	1.20		
P.		10.31	8.25	6.17	f 8.11	10.31	14.8	D	SAN LEANDRO	79.0	f 6.48	3.19	1.20	11.05	1.15		
P.		10.45	9.00	6.38	f 8.20	10.39	20.5	2S	HAYWARD	73.3	f 6.38	3.11	12.40	10.45	12.55		
		10.58	9.20	6.53	8.28	10.47	26.6		DECOTO	67.2	6.27	3.02	12.10 PM	10.28	12.35		
W. P.		11.15	9.45	7.20	f 8.36	f 10.55	29.7	DN	NILES	64.1	f 6.21	f 2.57	11.59 AM	10.20	12.25 AM		
P. Y.		11.18	9.50	7.23	8.38	10.57	30.5		NILES JUNCTION	63.3	6.14	2.52	11.30	10.03	11.59 PM		
P.		11.37	10.15	7.45	f 8.48	11.06	36.0	D	SUNOL	57.8	f 6.06	2.45	11.06	9.42	11.37		
P.		11.52 PM	10.40	8.00	f 8.57	11.15	41.5	D	PLEASANTON	52.3	f 5.57	2.38	10.40	9.27	11.05		
							42.7		S. P. Crossing	51.1							
							43.0		S. P. Crossing	50.8							
W. P.		12.17 AM	11.25 AM	8.15	f 9.08	11.25	47.6	D	LIVERMORE	46.2	f 5.47	2.30	10.15	9.08	10.40		
P.		12.42	12.04 PM	8.40	f 9.23	11.39	56.5		ALTAMONT	37.3	f 5.33	2.18	9.25	8.43	10.10		
P.		12.57	12.30	8.57	9.33	11.49	63.0		MIDWAY	30.8	5.17	2.04	8.57	8.10	9.33		
W. Y. P.		1.20	1.00	9.17	f 9.44	11.59 AM	71.8	2S	CARBONA	22.0	f 4.59	1.48	8.15	7.29	9.00		
P.		1.25	1.25	9.22	9.47	12.02 PM	73.9	D	LYOTH	19.9	4.54	1.45	7.50	7.17	8.48		
P.		1.32	1.41	9.30	9.51	12.06	76.8		FITZ	17.0	4.48	1.41	7.25	7.07	8.38		
P.		1.47	2.05	9.46	10.00	12.15	83.8		LATHROP	10.0	4.38	1.32	7.05	6.46	8.15		
P.		2.05	2.30	9.59	10.08	12.23	90.3		ORTEGA	3.5	4.28	1.23	6.50	6.28	7.50		
F. W. T. O. P. B. R. K.	7.10 PM	2.15 AM	2.40 PM	10.05 AM	f 10.11	12.26	92.0	DN	STOCKTON YARD	1.8	f 4.25	1.20	6.45 AM	6.20 PM	7.45 PM		
		3.40 AM		11.20 AM			93.2		A. T. & S. F. Crossing	0.6							
P. R. K.	7.20 PM	3.50 AM		11.30 AM	s 10.25 PM	s 12.35 PM	93.8	2S	STOCKTON	0.0	4.15 AM	1.15 PM		5.10 PM	7.00 PM		
	Arrive Daily	Arrive Daily	Arrive Daily Ex. Sunday	Arrive Daily	Arrive Daily	Arrive Daily			Leave Daily	Leave Daily		Leave Daily Ex. Sunday	Leave Daily	Leave Daily			
	.10	4.15	7.15	4.20	2.50	2.35			3.15	2.45		7.30	5.39	6.15			
	10.8	20.4	11.9	20.0	31.9	35.0			27.8	32.8		11.5	15.3	13.3			
									Time over Subdivision								
									Average Speed per Hour								

Westward Trains are superior to Eastward Trains of the same class.

Yard Limits: Oakland, Niles, Carbona and Stockton. Oakland Yard extends from W. P. Mole to Mile Post 13. Stockton Yard extends from yard limit board at bridge 89.82 to yard limit board 19 1/2 poles east of Mile Post 96.

Maximum speed, passenger trains 60, freight and mixed trains 40 miles an hour, except passenger trains will not exceed 35, freight and mixed trains 25 miles an hour between Bridges 23.93 and 24.31; passenger trains will not exceed 40 miles an hour on curve at Mile Post 29.4; passenger trains will not exceed 45, freight and mixed trains 30 miles an hour between Niles and Mile Post 37 and between Mile Posts 52 and 67, passenger trains reducing speed to 35, freight and mixed trains 25 miles an hour on curve at Bridge 35.09; on curves between Bridge 53.40 and Mile Post 55; on curve at Bridge 56.96 and over Bridge 64.43.

See page 6 for additional speed restrictions.

W. P. Mole is initial station for Nos. 2 and 4. Nos. 2 and 4 will obtain clearance card at Oakland Yard.

Trains must not exceed 15 miles an hour approaching and passing over S. P. crossings, Mile Post 7.2 and Mile Post 10.3, stopping if being used by a train or engine of that railroad.

Stockton is register station for first class trains only. At Stockton second class and extra trains will not require clearance card unless they receive train order. First class trains will not register at Stockton Yard. Operator at Stockton will transmit register of first class trains to operator at Stockton Yard, who will enter on register,

Nos. 1 and 2 will stop on flag at all stations in California for revenue passengers to or from points Salt Lake and East.

immediately verifying with Dispatcher on duty, for information of trains originating at Stockton Yard. The register of first class trains appearing on Stockton Yard register is the time at Stockton and does not indicate that a westward first class train has passed Stockton Yard.

Automatic Block System signals located as follows:

Eastward: Home signals Mile Post 29.4, Mile Post 30.0 and Mile Post 30.4.

Westward: Distant signal Mile Post 31.7; Home signals Mile Post 31.3 and Mile Post 30.3.

Trains moving from San Jose Branch: Switch indicators located at head block of east and west main track wye switches govern trains from wye to main track.

Table with columns for Class (Second Class, First Class), Station (Stockton, Flora Street, Kingdon, etc.), Time (Arrive Daily, Leave Daily), and Capacity of Sidings. Includes 'Time Table No. 17 June 19, 1932' and 'Distance from Oroville'.

Westward Trains are superior to Eastward Trains of the same class.

Yard Limits: Stockton, Sacramento, Marysville and Oroville. Stockton Yard extends from yard limit board at bridge 89.82 to yard limit board 19 1/2 poles east of Mile Post 96.

Maximum speed, passenger trains 60, freight and mixed trains 40 miles an hour, except passenger trains will not exceed 50, freight and mixed trains 35 miles an hour between Mile Posts 97 and 103 and between Mile Posts 119 and 124.

131; passenger trains will not exceed 50, freight and mixed trains 35 miles an hour on curve at Cleveland; at Mile Post 186.5 and between Graybros and Mile Post 189.

Passenger trains will not exceed 45 miles an hour on curve at Mile Post 201.9. See page 6 for additional speed restrictions.

Stockton, S. P. Tower "R" Street Sacramento and Oroville are register stations for first class trains only. First class trains will register by ticket at S. P. Tower "R" Street Sacramento and Oroville Yard.

At Flora Street, Track No. 7, located on north side of main track, west switch at Park Street, east switch immediately west of Harding Way, will be used as siding.

Rule 221 is modified as follows: Freight trains stopping at South Sacramento will not call for train order signal when it is found in STOP position but must obtain clearance card before leaving South Sacramento, when telegraph office is open.

See page 7 for Special Instructions applying to Joint Track, Marysville. Automatic Block System signals located as follows: At Oroville: Eastward signals at Mile Post 204.5 and 450 feet west of house track switch.

Westward signals at East siding switch and at Mile Post 205.

Nos. 1 and 2 will stop on flag at all stations in California for revenue passengers to or from points Salt Lake and East.

Fuel, Water, Fone, Table, Scale, Wye, Bulletin, Register Station, Standard Clock.	SECOND CLASS						FIRST CLASS		Distance from San Francisco	Time Table No. 17		Distance from Portola	FIRST CLASS		SECOND CLASS				Capacity of Sidings	
	84	62	82	96	54	98	2	4		June 19, 1932			1	3	61	95	81	97		
	Fast Freight	Fast Freight	Fast Freight	Local Freight	Fast Freight	Local Freight	Scenic Limited	Feather River Express		STATIONS Telegraph Offices and Calls			Scenic Limited	Feather River Express	Fast Freight	Local Freight	Fast Freight	Local Freight		
	Leave Daily	Leave Daily	Leave Daily	Leave Mon. Wed. & Fri.	Leave Daily	Leave Tues. Thurs. & Sat.	Leave Daily	Leave Daily		Arrive Daily	Arrive Daily		Arrive Daily	Arrive Tues. Thurs. & Sat.	Arrive Daily	Arrive Mon. Wed. & Fri.				
B. R. K. P.	11.30 PM	6.40 PM	11.10 AM	7.30 AM	5.40 AM			205.1	2S	OROVILLE	Vi	116.3	s 10.15 AM	s 12.15 AM		10.05 AM	12.30 PM	1.15 PM		55
P.	11.44	6.54	11.24	7.44	5.54			209.5		QUARTZ		111.9	10.06	12.04 AM		9.47	12.15	1.01		84
P.	11.56 PM	7.04	11.34	7.55	6.04			212.7		BIDWELL		108.7	10.00	11.56 PM		9.33	12.05 PM	12.51		70
P.	12.11 AM	7.19	11.49 AM	8.15	6.19			217.5		BLOOMER		103.9	9.50	11.43		9.15	11.49 AM	12.36		86
W. P.	12.32	7.40	12.10 PM	8.40	6.40			224.4	D	BERRY CREEK	Bk	97.0	9.36	f 11.24		8.40	11.25	12.10 PM		90
P.	12.53	8.01	12.31	9.22	7.01			231.4		DAVID		90.0	9.22	11.04		8.19	10.55	11.49 AM		65
P.	1.05	8.13	12.43	9.37	7.13			235.2		POE		86.2	9.13	10.54		8.07	10.40	11.37		80
F. W. P.	1.17	8.25	12.55	10.07	7.25			239.1	DN	PULGA	Bg	82.3	9.04	s 10.44		7.55	10.25	11.25		90
P.	1.32	8.40	1.10	10.30	7.40			243.7		ORESTA		77.7	8.54	f 10.27		7.40	9.55	11.03		82
W. P.	1.52	9.00	1.32	10.51	8.02			247.5		MERLIN		73.9	8.46	f 10.17		7.18	9.40	10.51		48
P.	2.10	9.17	1.50	11.20	8.19			253.1		TOBIN		68.3	8.34	f 10.00		6.58	9.15	10.34		58
P.	2.17	9.24	1.57	11.35 AM	8.29			255.3		CAMP RODGERS		66.1	8.29	f 9.53		6.51	9.05	10.27		85
W. P.	2.32	9.42	2.12	12.20 PM	8.44			260.0	2S	BELDEN	Bn	61.4	8.19	s 9.42		6.36	8.44	10.12		90
P.	2.47	9.57	2.27	12.50	8.59			264.6		RICH		56.8	8.09	f 9.24		6.21	8.22	9.57		52
W. P.	3.05	10.15	2.45	1.15	9.17			270.3		VIRGILIA		51.1	7.56	f 9.10		6.03	7.56	9.39		48
P.	3.16	10.26	2.56	1.35	9.28			273.7		TWAIN		47.7	7.48	f 9.00		5.51	7.35	9.28		65
P.	3.28	10.38	3.08	2.00	9.40			277.5		PAXTON	Xn	43.9	f 7.40	s 8.50		5.38	7.23	9.14		85
F. W. P. R. K. Y. T.	3.50	11.00	3.40	2.15 PM	10.05	8.15 AM		280.9	DN	KEDDIE	Kd	40.5	f 7.31	s 8.39		5.26	7.00 AM	9.00	11.55 AM	130
P.	4.03	11.14	3.54		10.19	8.31		284.5		SIERRA		36.9	7.22	f 8.23		4.56		8.31	11.40	85
P.	4.15	11.26	4.06		10.31	9.01		287.8	2S	QUINCY JUNCTION	Rt	33.6	s 7.16	s 8.16		4.46		8.21	11.25	74
P.	4.31	11.41	4.21		10.46	9.25		292.6		MASSAOK		28.8	7.06	f 8.00		4.31		8.06	10.46	85
W. P.	4.43	11.52 PM	4.32		10.57	10.10		296.6	DN	SPRING GARDEN	Sg	24.8	7.00	s 7.51		4.19		7.54	10.30	90
P.	4.58	12.07 AM	4.47		11.12	10.50		301.6	D	SLOAT	So	19.8	6.51	s 7.36		4.04		7.39	9.45	48
P.	5.10	12.19	4.59		11.24	11.24		305.4		TWO RIVERS		16.0	6.45	f 7.21		3.51		7.26	9.10	85
W. P.	5.25	12.34	5.14		11.39	11.59 AM		310.3	2S	BLAIRSDEN	Ba	11.1	s 6.37	s 7.10		3.36		7.11	8.50	54
P.	5.36	12.45	5.25		11.50 AM	12.15 PM		313.6		OLIO		7.8	6.29	s 7.00		3.26		6.56	7.55	62
P.	5.52	1.01	5.41		12.06 PM	12.35		318.7		MABIE		2.7	6.20	6.50		3.10		6.40	7.35	85
F. W. T. O. P. Y. B. R. K.	6.05 AM	1.15 AM	5.55 PM		12.20 PM	12.50 PM		321.4	DN	PORTOLA	Ki	0.0	6.15 AM	6.45 PM		3.00 AM		6.30 AM	7.20 AM	Yard
	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Mon. Wed. & Fri.	Arrive Daily	Arrive Tues. Thurs. & Sat.							Leave Daily	Leave Daily		Leave Daily	Leave Tues. Thurs. & Sat.	Leave Daily	Leave Mon. Wed. & Fri.	
	6.35	6.35	6.45	6.45	6.40	4.35				Time over Subdivision			4.00	5.30		7.05	5.30	6.45	4.35	
	17.7	17.7	17.2	11.2	17.4	8.8				Average Speed per Hour			29.0	21.1		16.4	13.8	17.2	8.8	

Westward Trains are superior to Eastward Trains of the same class.

Yard Limits: Oroville, Keddie and Portola. Oroville Yard extends from yard limit board 13 poles west of Mile Post 202 to yard limit board at Mile Post 206. Keddie Yard, Third Subdivision, extends from yard limit board 600 feet west of west siding switch to yard limit board 2600 feet east of east siding switch and on Fourth Subdivision, extends to yard limit board 200 feet west of west portal Tunnel No. 1; STOP board located 300 feet west of west portal Tunnel No. 1.

Maximum speed, passenger trains: Between Portola and Keddie, 40 miles an hour; between Keddie and David, 30 miles an hour; between David and Oroville, 35 miles an hour, except a speed of 30 miles an hour on curve at Mile Post 315 and on first curve east of Mile Post 315, and 25 miles an hour over Bridge 252.60 must not be exceeded.

Maximum speed, freight and mixed trains: Between Portola and Keddie, 30 miles an hour; between Keddie and David, 25 miles an hour; between David and Las Plumas, 30 miles an hour; between Las Plumas and Oroville, 25 miles an hour.

Freight and mixed trains will not exceed 20 miles an hour on curve at Mile Post 315, on first curve east of Mile Post 315 and over Bridge 252.60.

Eastward trains run with caution at Junction switch east end tunnel No. 32.

Mallet and Mikado engines will not exceed 20 miles an hour over Bridge 317.43.

Passenger trains must use 2, freight and mixed trains 4 minutes passing through Tunnel No. 35.

Oroville is register station for first class trains only. At Oroville second class and extra trains will not require clearance card unless train order signal is at STOP.

Keddie is register station for Nos. 95, 96, 97 and 98 only.

When passenger trains meet at Portola, pocket track in front of depot will be used by train taking siding, unless otherwise specified by train order.

Nos. 95, 96, 97 and 98 carry passengers.

The following will govern use of retainer valves on westward freight trains, Portola to Bloomer:

When the gross weight of train does not exceed 33 tons per car, turn up retainer valve on the first car back of engine and on each fourth car throughout the train. If the gross weight of train exceeds 33 tons and is less than 45 tons per car, turn up retainer valves on the five head cars and on every third car throughout the train. If the gross weight of train is 45 tons or more per car, turn up retainer valves on the five head cars and on every second car throughout the train. When retainers are turned up the handle will be placed in the low pressure position, which is horizontal. Should wheels show a tendency to heat, retainers must be alternated.

Automatic Block System signals located as follows:

At Oroville: Eastward signals at Mile Post 204.5 and 450 feet west of house track switch.

Westward signals at East siding switch and at Mile Post 205.

Nos. 1 and 2 will stop on flag at all stations in California for revenue passengers to or from points Salt Lake and East.

Fuel, Water, Phone, Table, Scale, Wye, Bulletin, Register Station, Standard Clock.	SECOND CLASS		FIRST CLASS		Distance from Keddie	Time Table 17 June 19, 1932		Distance from Bieber	FIRST CLASS		SECOND CLASS		Capacity of Sidings
	182	620		34		STATIONS Telegraph Offices and Calls			33		181	619	
	Western Pacific Fast Freight	Southern Pacific Local Freight		Southern Pacific Passenger		Arrive Daily	Arrive Daily		Western Pacific Fast Freight	Southern Pacific Local Freight			
F. W. P. T. Y. B. R. K.	4.00 PM			Leave Daily	0.0	DN	KEDDIE Kd	111.8			8.00 AM		Yard
P.	4.30				6.2		MOCCASIN	105.6			7.30		85
					7.62		I. V. Crossing	104.18					
					7.64		I. V. Crossing	104.16					
					8.38		I. V. Crossing	103.42					
					8.39		I. V. Crossing	103.41					
P.	4.55				8.6	D	CRESCENT MILLS Cm I. V. Connection	103.2			7.15		12
W. P.	5.20				14.7	D	GREENVILLE Gi	97.1			6.45		85
P.	5.35				17.5		MOHALA	94.8			6.15		85
W. P. Y.	6.10				25.4		ALMANOR	86.4			5.45		85
P.	6.35				32.4		LASSEN VIEW	79.4			5.13		85
P.	6.45				35.2		RED RIVER JUNCTION R. R. L. Connection	76.6			5.00		
F. W. P. Y. B. R. K.	7.30	11.45 AM		3.15 PM	39.4	Joint Track	DN WESTWOOD Wd S. P. Connection	72.4	s 12.18 PM		4.40	9.30 AM	Yard
P. R.	7.50	12.01 PM		f 3.22 PM	43.5		D MASON Mn	68.3	12.11 PM		4.10	9.17 AM	
P.	7.55				44.1		ROBBERS CREEK	67.7			4.05		85
					50.1		L. L. & B. R. R. Crossing	61.7					
					50.4		L. L. & B. R. R. Crossing	61.4					
W. P. Y.	8.35			Time of No. 34 at Westwood applies at Passenger Station	52.5		NORVELL	59.3	Time of No. 33 at Westwood applies at Passenger Station		3.40		85
P.	9.05				62.9		LODGEPOLE	48.9			3.10		85
W. P. Y.	9.50				76.4		HALLS FLAT	35.4			2.30		85
P.	10.20				84.2		JELICO	27.6			1.55		85
P.	10.45				90.2		WILLOW SPRINGS	21.6			1.30		85
W. P.	11.10				94.8		LITTLE VALLEY	17.0			1.10		85
P.	11.40 PM				100.9		DIXIE	10.9			12.45		85
P.	12.10 AM				109.5		PIT RIVER	2.3			12.10 AM		85
F. W. P. O. Y. B. R. K.	12.30 AM				111.8	DN	BIEBER B	0.0			11.50 PM		Yard
	Arrive Daily	Arrive Daily Ex. Sunday		Arrive Daily					Leave Daily		Leave Daily Ex. Sunday		
	8.30	0.16		0.07			Time over District		0.07		8.10	0.13	
	13.2	15.4		35.1			Average Speed per Hour		35.1		13.7	18.9	

Westward Trains are superior to Eastward Trains of the same class.

Yard Limits: Keddie, Red River Jct., Westwood and Bieber. Keddie Yard, Fourth Subdivision, extends to yard limit board 200 feet west of west portal Tunnel No. 1; STOP board located 300 feet west of west portal Tunnel No. 1; Third Subdivision, extends from yard limit board 600 feet west of west siding switch to yard limit board 2600 feet east of east siding switch. Bieber Yard extends from yard limit board 4000 feet west of west switch Bieber to yard limit board 3.1 miles east of Bieber passenger station.

Maximum speed, between Keddie and Crescent Mills, 20 miles an hour; between Crescent Mills and Greenville, 35 miles an hour; between Greenville and Red River Jct., 20 miles an hour; between Red River Jct. and Halls Flat, 35 miles an hour; between Halls Flat and Pit River, 20 miles an hour and between Pit River and Bieber, 35 miles an hour. On curves or where other conditions require, speed must conform to provisions of Rule 855.

Southern Pacific Co. and Red River Lumber Co. trains will be governed by Western Pacific R. R. Co. Time Table and Rules and Regulations of the Transportation Department.

Only one stop need be made for I. V. R. R. wye crossings, Mile Post 7.62 and 7.64 and for I. V. R. R. main line and I. V. R. R. Standard Oil Spur crossings Mile Post 8.33 and 8.39.

At Mason, train order signal governs Western Pacific R. R. Co. trains only. Westward Southern Pacific Co. trains must obtain clearance card at Mason.

Mason is register station for Nos. 33, 34, 619 and 620 only. Nos. 33, 34, 619 and 620 may register by ticket at Mason, when there is an operator on duty.

At Mason, before a westward Western Pacific R. R. Co. train fouls Junction switch, brakeman must go back far enough on Southern Pacific Co. track to provide full protection.

Eastward passenger trains will make running air brake test approaching Halls Flat and westward passenger trains will make running air brake test approaching Almanor as prescribed by Rules 1157 and 1158.

Westward freight and mixed trains will make rear end test at Almanor and eastward freight and mixed trains at Halls Flat as prescribed by Rule 1156.

On eastward freight and mixed trains, before leaving Halls Flat and on westward freight and mixed trains before leaving Almanor, enginemen must be notified as to number of loads and empties in train and whether or not all air brakes are cut in and working.

On grades, following will govern use of retainer valves:

All retainers will be turned up between following points:

Westward: Between Almanor and Greenville.

Eastward: Between Halls Flat and Little Valley.

Between following points an understanding must be had between Conductor and engineer as to number of retainer valves necessary to control train and retainer valves must be used accordingly:

Westward: Between Dixie and Little Valley,
Between Norvell and Almanor,
Between Moccasin and Keddie.

Eastward: Between Dixie and Pit River.

Normal position of switches:

Keddie: Switch leading from east leg of wye to Fourth Subdivision, lined for east leg of wye.

Red River Jct.: Junction switch lined for Western Pacific R. R. Co. main track.

Mason: Junction switch lined for Southern Pacific Co. main track.

Fuel, Water, Fone, Table, Scale, Wye, Bulletin, Register Station, Standard Clock.	SECOND CLASS		Distance from Niles	Time Table No. 17 June 19, 1932		Distance from San Jose Alameda St. Freight Station	SECOND CLASS		Capacity of Sidings
	178 Freight	Leave Daily		STATIONS Telegraph Offices and Calls	177 Freight		Arrive Daily		
W. P. R.	12.30AM	0.0	DN NILES On	23.8	10.45PM	50			
Y. P.	12.40	0.8	NILES JUNCTION	23.0	10.25				
P.	1.00	4.1	IRVINGTON	19.7	10.10	20			
	1.15	7.6	WARM SPRINGS	16.2	9.55	Spur 1W 3			
P.	1.35	11.7	D MILPITAS Mi	12.1	9.40	35			
	1.45	14.9	BERRYESSA	8.9	9.25				
		15.2	Peninsular R. R. Crossing	8.6					
P. K.	2.00	17.7	D SAN JOSE East Santa Clara St. San Jose Street R. R. Crossing	6.1	9.10				
P. W. T. F. R. B. O.	2.10AM	18.3	2S SAN JOSE YARD Sx	5.5	9.00PM	Yard			
		20.3	S. P. TRANSFER	3.5					
		20.4	VALBRICK S. P. Crossing	3.4					
		23.1	S. P. CROSSING	0.7					
		23.8	SAN JOSE Alameda St. Freight Station	0.0		Yard			
	Arrive Daily				Leave Daily				
	1.40		Time over Subdivision		1.45				
	11.0		Average Speed per Hour		9.2				

Westward Trains are superior to Eastward Trains of the same class.

Yard Limits: Niles and San Jose. Niles yard extends to yard limit board 3000 feet east of wye switch at Niles Jct. San Jose yard extends to yard limit board M. P. 16.2.

Maximum speed, passenger trains 30, freight and mixed trains 25 miles an hour.

Trains must stop at STOP board before passing over Peninsular Railroad Crossing at M.P. 15.2 and San Jose Street Railway Crossing at San Jose; maximum speed 6 miles an hour over these crossings.

Maximum speed 5 miles an hour over crossings, McKee Road, just west of passenger depot, East Williams Street, just west of round house lead, and 24th Street, San Jose.

Maximum speed 6 miles an hour over San Jose Street Railway crossing at Willow Street and Peninsular R. R. crossings, Coe Avenue, San Carlos Street and Park Avenue, between San Jose, East Santa Clara Street and San Jose, Alameda Street.

Maximum speed 12 miles an hour within city limits, San Jose.

San Jose Branch trains have no Time Table superiority between Niles Junction and Niles. Their movement between these points will be governed by block signals and Rule 93. Time shown at Niles is for information only.

Fuel, Water, Fone, Table, Scale, Wye, Bulletin, Register Station, Standard Clock.	Time Table No. 17 June 19, 1932		Distance from Moy	STATIONS Telegraph Offices and Calls		Capacity of Sidings
	Distance from Carbona	Ob				
W. Y. P.	0.0	DN CARBONA Ob	4.2		46	
	1.7	KERLINGER	2.5		Spur 1W 8	
O. P.	3.4	RIVER ROCK	0.8		Spur 1W 27	
	4.2	MOY	0.0		No Siding	

Westward Trains are superior to Eastward Trains of the same class.

Derails on main track M. P. 3.3 and 240 feet west and 885 feet east of Stock Yards Moy. Maximum speed 12 miles an hour. Cars on main track east of River Rock not protected.

SECOND SUBDIVISION "A"—TERMINOUS BRANCH.

Fuel, Water, Fone, Table, Scale, Wye, Bulletin, Register Station, Standard Clock.	Eastward		Distance from Terminous Jct.	Time Table No. 17 June 19, 1932		Distance from Terminous	Westward	
	Y. P.	W. Y.		STATIONS Telegraph Offices and Calls	Capacity of Sidings			
Y. P.			0.0	TERMINOUS JCT.	7.8	20		
			3.5	GARDEN	4.3	8		
			6.6	GRASS	1.2	6		
W. Y.			7.8	D TERMINOUS Us	0.0	Yard		

Westward Trains are superior to Eastward Trains of the same class.

Maximum speed, 12 miles an hour between Terminous Jct. and Garden and 10 miles an hour between Garden and Terminous.

SPECIAL RULES

**ADDITIONAL SPEED RESTRICTIONS
GENERAL**

Silk and express trains must conform to passenger train speed restrictions.
 Maximum speed, trains handling steam derricks, steam shovels, cranes, rotary plows or pile drivers, 25 miles an hour on First and Second Subdivisions and 20 miles an hour on Third and Fourth Subdivisions.
 Speed of engines backing must not exceed 20 miles an hour on straight track. On curves and where track conditions are unfavorable, speed must be reduced still further to a rate consistent with safety.
 Maximum speed, passenger trains 40, freight and mixed trains 25 miles an hour over interlocking crossings.
 Maximum speed, Consolidation and Mikado engines handling passenger trains, 50 miles an hour.
 Maximum speed, Mallet engines, 201 to 210 inclusive, 30 miles an hour.
 Maximum speed, Mallet engines, 251 to 256 inclusive, 20 miles an hour, except a speed of 5 miles an hour must not be exceeded through cross-overs and turn-outs.
 Engines running light, except Mallet engines, must not exceed the speed prescribed for freight trains, except as follows: When necessary to meet some emergency, dispatchers may instruct engineers of lone engines to run not to exceed 40 miles an hour on main line, except that a speed of 35 miles an hour between Portola and Keddie, 30 miles an hour between Keddie and Berry Creek, and 35 miles an hour between Berry Creek and Oroville must not be exceeded.
 Engines running light on Branches must conform to speed prescribed for freight trains on each Branch, except in an emergency, dispatchers may instruct that a speed not exceeding maximum for passenger trains on that particular Branch may be made.

FIRST SUBDIVISION

Maximum speed, passenger trains 15, freight and mixed trains 10 miles an hour over, along or upon any of the public streets or highways within Oakland city limits, except all trains must not exceed 8 miles an hour between Washington and Franklin streets and 10 miles an hour between Mile Post 8.7, just west of 21st Avenue and Mile Post 9.8, just east of Fruitvale Avenue. Traffic light signals at 23rd Avenue and East 12th Street, Mile Post 9.0, should show green indication on East 12th Street when an engine or car reaches a point 220 feet east or west of 23rd Avenue. In absence of light in signals, speed must be still further reduced within these limits.
 Maximum speed, passenger trains 20, freight and mixed trains 15 miles an hour between bridge just west of San Leandro depot and Williams Street, 5 blocks east of San Leandro depot.
 Passenger trains must use 1 minute and 30 seconds, freight and mixed trains 3 minutes passing through Tunnel No. 1.
 Maximum speed, all trains, 15 miles an hour within city limits, Pleasanton and Livermore.
 Maximum speed, passenger trains 20, freight and mixed trains 15 miles an hour over San Joaquin River drawbridge, Mile Post 80.28.
 Maximum speed, passenger trains 40, freight and mixed trains 25 miles an hour through interlocking plant Ortega, Mile Post 90.3.
 Maximum speed, all trains, 8 miles an hour between A. T. & S. F. crossing, Mile Post 93.2 and Stockton Depot.
SECOND SUBDIVISION
 Maximum speed, all trains, 8 miles an hour between Stockton Depot and Park Street, Stockton.
 Maximum speed, passenger trains 20, freight and mixed trains 15 miles an hour over Mokelumne River drawbridge, Mile Post 116.4.
 Maximum speed, all trains, 15 miles an hour between "C" and "Y" Streets, Sacramento.

MISCELLANEOUS

GENERAL

When two engines are double-heading and lead engine is to be cut off train, air will be set by lead engine before detached, after which train engine will fully release air brakes and regain full working pressure before proceeding. When air connections have not been disturbed back of engine next to train, it will not be necessary to make rear end test as prescribed by Rule 1156.
 When using helper engine on rear of train as pusher, it will not be necessary, after detaching helper from train, to make rear end test as prescribed by Rule 1156.
RULE 927. FIRST AND SECOND SUBDIVISIONS: When conditions are favorable and in judgment of Conductor it is safe to do so, run may be made for train inspection on freight and mixed trains from one water stop to next water stop, excepting a distance of 70 miles must not be exceeded between inspections.
THIRD AND FOURTH SUBDIVISIONS: When conditions are favorable and in judgment of Conductor it is safe to do so, run may be made on freight and mixed trains without stopping for train inspection for a maximum distance of 45 miles, except a standing car to car or careful rolling inspection must be made on westward freight and mixed trains at Blairsden, Two Rivers or Sloat and at Almanor and Greenville and on eastward freight and mixed trains at Keddie or at some point between Keddie and Spring Garden and at Halls Flat and Little Valley.
 When Mallet or Mikado engines are in a train with another engine of any class, either in service or dead in train, they must be separated by sufficient cars to avoid more than one engine passing over either a bridge or trestle at the same time.
 At Oakland, Stockton, Sacramento and Marysville, City Ordinance forbids the use of engine whistle except when necessary.
 Where train line has not been separated, air test as prescribed by Rule 1155 need not be made at Terminals.
 Headlights and markers must be burning through Tunnels 1, 4, 5, 23, 33 and 35.

FIRST SUBDIVISION

Street crossing Third and Broadway, Oakland, must not be blocked by passenger trains regardless of the number of cars in train.

Tracks between a point 100 feet west of the west line of Washington Street and 100 feet east of the east line of Franklin Street, Oakland, must not be used for meeting or passing trains.

Joint W. P. and S. P. drill track between Melrose and Elmhurst must not be used for meeting or passing trains.

Any engine or cars moved over spur serving California Packing Corporation near 85th Ave., Oakland, must be under control and highway traffic protected by member of train crew.

At Hayward, mikado engines must not cross C Street on Farm Products spur and on Poultry Producers spur.

Westward trains take full tank of water at Niles.

At Hayward, Pleasanton and Livermore, east siding switch is west of passenger station.

At Carbona, crossover switch located 700 feet east of station is the west siding switch.

Tower at A. T. & S. F. crossing Stockton, Mile Post 93.2, is equipped with electric siren. Two short blasts repeated several times is a warning to yard and trainmen to clear plant.

At Stockton Yard, Track No. 1, west switch located at Mile Post 91 and east switch located twelve poles west of Mile Post 92, is the siding to be used when first-class trains meet at Stockton Yard.

At Stockton Yard, track No. 9 will be used as run-around track for movement of engines between round house and west end of yard.

Westward freight trains will enter Stockton Yard at lead switch located immediately west of South Street. Eastward freight trains will enter Stockton Yard at lead switch Mile Post 91.

SECOND SUBDIVISION

Bridge over Smith Canal, North Channel Line, Stockton, will not clear man on top of high car.

The first street crossing west of South Sacramento must not be blocked by freight trains taking water, oil, or doing work at South Sacramento between 7.00 A.M. and 6.00 P.M. Eastward freight trains will, when necessary to avoid blocking this crossing, leave train west of crossing while taking water or oil, or switching.

At South Sacramento, Nos. 3 and 4 will stop with baggage car opposite Shop platform instead of at Yard Office.

Engines must not go beyond frog on Cliff House spur Marysville.

JOINT TRACK MARYSVILLE

Sacramento Northern trains will operate over Western Pacific main track between Sacramento Northern connection with Western Pacific main track, located 356 feet east and 355 feet west of bridge 178.18, Yuba River, Marysville. Sacramento Northern freight trains will operate over Western Pacific siding between west switch and switch leading to Sacramento Northern track opposite Western Pacific passenger station Marysville. These tracks are designated as Joint Tracks.

Automatic Interlocking Signals governing Joint Track located as follows:

WESTERN PACIFIC RAILROAD CO.

EASTWARD—Home Signal 789 feet west of bridge 178.18; normal position stop. Distant Signal 2500 feet west of Home Signal; normal position caution.

Home Signal 724 feet east of bridge 178.18; normal position clear. Distant Signal 789 feet west of bridge 178.18; normal position caution.

WESTWARD—Home Signal east end of bridge 178.79; normal position clear. Home Signal 724 feet east of bridge 178.18; normal position stop.

Eastward Signal located 789 feet west of bridge 178.18, will give clear indication when approaching train reaches a point within 3500 feet from signal, provided block is clear and will go to stop position when forward wheels of an engine or car pass the signal.

Westward Signal located 724 feet east of bridge 178.18, will give clear indication when approaching train reaches a point within 500 feet from signal, provided block is clear and will go to stop position when forward wheels of an engine or car pass the signal.

SWITCH INDICATORS located as follows:

- Switch west end of siding.
West end of main track switch leading to interchange track.
East end of main track switch leading to interchange tracks.
West end of cross-over leading from main track to siding.
Switch east end of High Line Track, located 1400 feet west of Mile Post 180.

SACRAMENTO NORTHERN RAILWAY

EASTWARD—Home Signal 542 feet west of bridge 178.18, located at left of track; normal position stop.

WESTWARD—Home Signal 525 feet east of bridge 178.18; normal position stop.

Home Signals located 542 feet west of bridge 178.18 and 525 feet east of bridge 178.18, will go to clear position when junction switch and derails are lined for Sacramento Northern track, provided block is clear and will go to stop position when forward wheels of an engine or car pass the signal.

SWITCH INDICATORS located as follows:

- Main track switch leading to Sand Pit, west of bridge 178.18.
Switch leading from Sand Pit, located 68 feet east of Western Pacific main track west of bridge 178.18.

These indicators govern movement of Sacramento Northern trains to and from Sand Pit across Western Pacific main track and to Sacramento Northern main track. In addition to stopping at STOP boards, Sacramento Northern trains or motors moving to or from Sand Pit, must have a clear indication by switch indicators before proceeding onto or over Western Pacific crossing, located 489 feet west of bridge 178.18.

No engine, car, motor or train of Western Pacific or Sacramento Northern shall be operated over railroad crossing located 752 feet east of bridge 178.18 where Western Pacific house track crosses Sacramento Northern track, without being brought to a stop at STOP board and preceded over crossing by a member of crew who shall determine first that it is safe to proceed. STOP boards are located on each side of this crossing 100 feet from crossing. Sacramento Northern trains and yard motors must approach this crossing with caution and not move onto or over crossing until determined first that it is safe to proceed.

DERAILS.—Derailing switches, pipe connected and operated with main track switches, located as follows:

On Western Pacific siding 193 feet east of west switch.
On Sacramento Northern track 182 feet west of Junction Switch west of bridge 178.18 and 157 feet east of Junction Switch east of bridge 178.18.

NORMAL POSITION OF SWITCHES.—Junction switches must be locked for Western Pacific main track when not in use.

MOVEMENT OF TRAINS.—Movement of trains over Joint Track will be governed by Rule 663 and made in accordance with indication of block signals, regardless of right or class. All trains of both companies must approach and pass through limits of Joint Track with caution, not exceeding a speed of 15 miles an hour.

In using Joint Track freight trains should avoid delays to other trains of either Company.

THIRD SUBDIVISION

Engines must not use siding at Blinzig.

Water may be obtained at Blinzig.

Engines must not use Spur at Belden beyond Mile Post 260.

Derail located on Gray's Flat Spur, 322 feet from main line switch.

At Twain, the extreme west switch is west siding switch.

Mikado engines must not use house or back track Paxton beyond point of frog.

Re-inforcing steel in Tunnel 32 will not clear man on top of box car and is close clearance for engines 251 to 256 inclusive.

At Keddie, engines 251 to 256 inclusive, must not use tracks other than main track, siding, house track, Fourth Subdivision freight and passenger leads, when it can be avoided. If necessary to use other tracks, movements must be protected in such a way that engines of 251 to 256 class will not meet or attempt to pass other engines on these tracks.

When calling in flagman from east on Fourth Subdivision at Keddie, enginemen will sound six long blasts of whistle.

Passengers and LCL freight for Cresta will be handled at Section House, just east of east switch; Camp Rodgers at Platform just east of east switch; Sierra at Mile Post 285 1/2; Two Rivers at Station Shelter, just east of east switch.

Passengers and LCL freight for Gray's Flat will be handled at Station Shelter Mile Post 273.1 and carload freight at Spur Mile Post 272.6.

Movement over Mill track between Blairsden and Graeagle must be made with air coupled and operative throughout.

Derail on Mill spur between Blairsden and Graeagle located 982 feet east of Feather River bridge.

Hayes derail located on Delleker Spur, 285 feet from main line switch.

FOURTH SUBDIVISION

When calling in flagman from east on Fourth Subdivision at Keddie, enginemen will sound six long blasts of whistle.

When cars are set out between Almanor and Greenville or between Halls Flat and Little Valley in addition to provisions of Rule 840 unless there is a derail, lower car must be chained to rail and Dispatcher notified.

Headlights and markers must be burning through Tunnels 1, 2, 3, 6 and 8.

At Westwood, track No. 1 will be used as siding.

Trains or engines using main track over Veneer Plant crossing east of passenger station and Third Street crossing, west of passenger station, Westwood, will reduce speed sufficiently to be able to stop before striking anything that might be on or is about to use these crossings and between the following times, movement over these crossings must be preceded by flagman:

- 11.30 a.m. and 11.40 a.m.
11.58 a.m. and 12.10 p.m.
4.00 p.m. and 4.10 p.m.
5.58 p.m. and 6.10 p.m.
7.30 p.m. and 7.30 a.m.

Movement of trains and engines on tracks other than main track, over any crossings in Westwood Yard must be preceded by flagman.

When trains meet at Westwood, crossings at Veneer Plant, east of passenger station and Third Street, west of passenger station, must not be blocked.

Derail installed on west end R. R. L. Co. electric siding Westwood Yard must be kept in derail position when cars are on siding.

At Bieber, Highway crossing signals at Highway crossing just east of Bieber passenger station. Signals set at STOP when trains enter approach sections. Westward approach section is 1000 feet long and eastward approach section 450 feet long. Signals will clear when trains pass over crossing if there is no following train on approach sections. When switching over this crossing entire train should not be moved east of crossing, as this allows signals on highway to show clear and make it possible for vehicles to be driven into side of train without having passed a stop signal. It is necessary for car or engine to remain west of insulated joint, located just east of crossing, in order to hold Highway signals in stop position. Trainmen will continue to flag this crossing when switching over Highway.

GRADES ON FOURTH SUBDIVISION

Table with columns: Between, Per Cent of Grade, Eastward, Westward. Lists various mileposts and their corresponding grades and directions.

INTERLOCKING PLANTS AND SIGNALS

S. P. crossing M. P. 5.2. Interlocked. Home signals 450 feet east and 970 feet west of crossing. Distant signals 2000 feet east and 1630 feet west of home signals.

S. P. crossing M. P. 5.8. Interlocked. Eastward trains on main track governed by two-arm home signal 700 feet west of crossing, upper arm governs main track eastward, lower arm governs movement main track to siding eastward. No distant signal. Westward trains on main track and siding governed by signals on bracket post 750 feet east of crossing. No distant signal. Bracket post is equipped with suspended signal under main track signal which governs movement main track to track No. 1 westward.

S. P. crossing M. P. 6.7. Interlocked. Eastward trains on main track governed by home signal 500 feet west of crossing. Eastward trains on siding governed by high dwarf signal 250 feet west of crossing on north side of Wellman-Peck Company spur. Westward trains governed by signals on bracket post 500 feet east of crossing. Home signal arm governs trains on main track and dwarf signal governs trains on siding. No distant signals.

S. P. crossing M. P. 7.2. No signals. (See footnote, page 2.)
S. P. crossing M. P. 7.8. Interlocked. Home signals 450 feet east and west of crossing. One distant signal 2000 feet east of home signal.

S. P. crossing M. P. 10.3. No signals. (See footnote, page 2.)
S. P. crossing M. P. 10.6 and M. P. 10.7. Interlocked. Home signal 450 feet west of crossing M. P. 10.6. Distant signal 2000 feet west of home signal. Home signal 685 feet east of crossing M. P. 10.7. Distant signal 2500 feet east of home signal.

S. P. crossing M. P. 13.7. No signals.
S. P. crossing M. P. 30.3. Interlocked. Home signals 450 feet east and west of crossing. Distant signals 2160 feet east and 1280 feet west of home signals.

S. P. crossing M. P. 42.7. Interlocked.
S. P. crossing M. P. 43.0. Interlocked.

Towerman on duty, crossings M. P. 42.7 and M. P. 43.0 from 7.00 a. m. until 12.00 noon and from 1.00 p. m. until 4.00 p. m. daily except Sunday. During these hours, signals will be operated by Towerman in accordance with Rules 600 to 686-A inclusive. During hours when there is no towerman on duty, normal position of signals governing W. P. trains over these crossings will be proceed and if S. P. train makes movement from their line to San Ramon Branch in either direction, signal maintainer will operate switches and signals to protect such movement.

Home signals 480 feet east of crossing at M. P. 43.0 and 480 feet west of crossing at M. P. 42.7. Distant signals 2000 feet east and west of home signals. Switch indicator located at west switch Radum gives warning of approach of train in either direction. See Rule 512.

S. P. crossing M. P. 73.9. Interlocked. Home signal 800 feet west of crossing. Distant signal 2840 feet west of home signal. Home signal 600 feet east of crossing. Distant signal 2640 feet east of home signal. Two-arm home signal 210 feet west of crossing. Upper arm governs main track westward over cross-over switch; lower arm governs movement from main track through cross-over to siding. Dwarf signal located between main track and interchange track, 230 feet west of main track switch, governs movement from siding to main track.

S. P. crossing M. P. 83.8. Interlocked. Home signals 650 feet east and west of crossing. Distant signals 2640 feet east and west of home signals.

S. P.-T. S. crossings M. P. 90.3. Interlocked.
Home signal 925 feet west of junction switch governs eastward trains on W. P. main track.

Two-arm home signal 700 feet east of junction switch: Upper arm governs westward trains on W. P. main track; lower arm governs movement through cross-over. Distant signals 3000 feet east and west of home signals.

Eastward T. S. trains governed by two-arm dwarf home signal 400 feet west of junction switch; upper arm governs movement to T. S. and over S. P. crossing, or through cross-over to W. P. main track; lower arm governs movement to W. P. siding. Trainmen will line derail.

Westward T. S. trains governed by home signal 450 feet east of S. P. crossing. This signal governs movement over S. P. crossing to T. S. main track. No distant signals.

Hand operated derails with electric locks under control of towerman installed on W. P. siding and stock yards track.

Trains desiring to move to stock yards track will sound proper whistle signal and when signal placed at proceed or prescribed hand signal given by towerman, may proceed to entrance switch and after trainmen have lined switch and derail, movement may be made.

Movement from stock yards track or from W. P. siding, will be made only on receipt of hand signal from towerman. After this signal received, trainmen will line derail and if movement is from stock yards, will also line switch and derail before movement is made.

W. P. siding derail and stock yards switch and derail must be restored to normal position by trainmen immediately after completing movement.

At west end Stockton Yard, when either switch of cross-over is lined for cross-over movement, home and distant signals on W. P. main track are held at stop.

Following are whistle signals:

To or from W. P. siding, two long, two short.

To or from stock yards, one long, one short, one long.

To W. P. main track, one long.

To T. S. main track, one long, one short.

A. T. & S. F. crossing M. P. 93.2. Interlocked. Home signals 450 feet east and west of crossing. One distant signal 2450 feet west of crossing.

S. P. crossing M. P. 93.8. Interlocked. Home signals 450 feet east and west of crossing. No distant signals.

S. P. crossing M. P. 95.1. Interlocked. Home signals 650 feet east and west of crossing. One distant signal 3000 feet east of home signal.

C. C. T. and S. N. crossing M. P. 137.5. Interlocked. Home signals 450 feet east and west of crossing. One distant signal 1480 feet west of home signal. Switch indicator located at head block of west switch old Ice House track, Sacramento, governs movement from old Ice House track to main track.

Hayes derail on old Ice House track, located 171 feet east of west switch, is pipe connected to main track switch and switch must not be closed until rear of train has passed derail.

Maximum speed, 15 miles an hour within limits of home signals, this crossing.

If no cause of signals being at STOP is seen or if there is a train on conflicting route, with no indication it is to proceed immediately, be governed by Rule 663.

Cars must not be left standing within home signal limits unless coupled to other cars or an engine standing outside of limits.

S. P. crossing M. P. 138.0. Interlocked. Trains governed by two-arm home signals located 796 feet east and 700 feet west of crossing. Upper arms govern main track, lower arms govern legs of wye. Following are whistle signals:

Main line to wye, either leg, one long, one short.

Wye to main line, either leg, one short, one long.

S. N. crossing M. P. 139.2. Interlocked. Home signals 480 feet east and 450 feet west of crossing. No distant signals. Switch indicator located at head block of Haggin Transfer main track switch, just east of subway, Sacramento, governs movement from Haggin Transfer track to main track.

Hand operated derail on Haggin Transfer track, located 159 feet east of west switch. Maximum speed, 15 miles an hour within limits of home signals, this crossing.

If no cause of signals being at STOP is seen or if there is a train on conflicting route, with no indication it is to proceed immediately, be governed by Rule 663.

Cars must not be left standing within home signal limits unless coupled to other cars or an engine standing outside of limits.

S. N. crossing M. P. 140.8. No signals.

S. N. crossing Mile Post 152.5. Automatic interlocked. Home signals 600 feet east and west of crossing. Distant signals 3000 feet east and west of distant signals. Preliminary approach circuits extend 3000 feet east and west of distant signals.

Normal indication of interlocking home signals STOP.

When train enters approach circuit, home and distant signals should change to proceed.

Speed of engine must not exceed 20 miles an hour between home signal and crossing, consuming not less than 20 seconds between home signal and crossing.

If no cause for signals being at STOP is seen or if there is a train on intersecting track standing outside of home signals, with no indication it is to proceed immediately, flagman must be sent ahead to operate clockwork time release located in box at crossing which is secured with switch lock. Instructions for operation of clockwork time release are inside of box and are as follows:

(a) Release must not be operated when trains or engines are between home signals or seen to be approaching on intersecting track.

(b) To operate clockwork time release, turn knob to right to extreme position, then let go of knob and allow automatic release mechanism to run down, which will require four minutes. When knob is turned to extreme position and release mechanism starts to operate, a red pilot light, located near clock release, should light immediately indicating that home signals on intersecting line are in STOP position. In meantime clockwork time release will run down and home signal should change from STOP to PROCEED WITH CAUTION.

NOTE: Where home signals are involved in automatic block signal territory, flagman, upon receiving red indicator light, must lock box and proceed in accordance with Automatic Block System Rules and where no automatic block signals are involved, flagman will remain at crossing until train arrives.

In case pilot light fails to appear, movement must be protected in each direction on intersecting line.

(c) In case operation of release does not change home signal indication from STOP to PROCEED WITH CAUTION after pre-determined time has elapsed, a repeater red indicator light located at home signal should then light up, indicating home signals on intersecting line are in STOP position.

S. N. crossing M. P. 178.1. Automatic interlocked. (See Special Rules, page 6.) S. P. crossing M. P. 179.1. Interlocked. Home signals 414 feet east and 474 feet west of crossing. Two-arm distant signal 1210 feet east of home signal and 1040 feet west of home signal. Two-arm home signal 1624 feet east of crossing protects movement over and to High Line and S. P. Interchange tracks. Distant signal 2582 feet east of home signal. Switch and derail to S. P. interchange track, switch and derail to High Line track and derail on Stock Yard track within interlocking limits are hand-operated and electrically locked and permission must be obtained from Towerman for each movement in or out of these tracks, switches and derails to be immediately returned to normal position after movement made.

S. P. crossing M. P. 180.2. Interlocked. Home signals 650 feet east and west of crossing. Distant signals 3100 feet east and 2650 feet west of home signals.

SAN JOSE BRANCH
Peninsular R. R. crossing, M. P. 15.2. No signals.

San Jose Street Railway Company crossing, San Jose, East Santa Clara St. No signals. S. P. crossing M. P. 20.4. Interlocked. Two-arm home signal 812 feet west of crossing. Upper arm governs movement of trains on main track; lower arm governs movement of trains to Fifth Street spur. Home signal 454 feet east of crossing. No distant signals.

S. P. crossing M. P. 23.1. Interlocked. Home signals 455 feet east and 539 feet west of crossing. No distant signals.

TUNNEL SIGNALS
Automatic Block System signals govern track through Tunnels 1, 2, 4 and 35. Tunnels 1 and 2. Home signal 1500 feet west of west portal Tunnel 1. No distant signal. Home signal 200 feet east of east portal Tunnel 2. Distant signal 1800 feet east of home signal.

Tunnel 4. Home signals 1716 feet east and 1150 feet west of Tunnel. No distant signals.

Tunnel 35. Home signals 400 feet east and 1000 feet west of Tunnel. One distant signal 2000 feet east of home signal.

DRAWBRIDGE SIGNALS
San Joaquin River drawbridge M. P. 80.28. Interlocked. Home signals 650 feet east and 600 feet west of bridge indicate position of draw. Distant signals 2000 feet east and west of home signals.

Mokelumne River drawbridge M. P. 116.4. Interlocked. Home signals 500 feet east and west of bridge indicate position of draw. One distant signal 2500 feet east of draw.

TONNAGE RATING
Consolidation Engines Mikado Engines Mallet Engines 201 to 210 inclusive 251 to 256 inclusive

EASTWARD:
First Subdivision..... 1650 tons 2500 tons
Second Subdivision..... car limit car limit
Third Subdivision..... 1250 tons 1800 tons 2200 tons 4000 tons
Fourth Subdivision:
Keddie to Almanor..... 617 tons 858 tons 1170 tons
Almanor to Little Valley..... 896 tons 1247 tons 1688 tons
Little Valley to Bieber..... 796 tons 1113 tons 1511 tons

WESTWARD:
First Subdivision..... 1400 tons 2350 tons
Second Subdivision..... car limit car limit
Third Subdivision..... car limit car limit car limit car limit
Fourth Subdivision:
Bieber to Halls Flat..... 756 tons 1051 tons 1427 tons
Halls Flat to Keddie..... 1254 tons 1745 tons 2354 tons

The rating for passenger engines on Second Subdivision will be 2200 tons and on other Subdivisions, 65 per cent of consolidation engine rating.

Tonnage rating based on maximum grade on each Subdivision. Between points where grades are less than maximum, greater tonnage can be handled and conductors and enginemen will be expected to fill trains to capacity of engines.

WATCH INSPECTORS
S. A. Pope, Manager of Time Service, San Francisco.
San Francisco, Calif. I. S. Preston, R. 210 Phelan Bldg.
San Francisco, Calif. M. S. Groud, 210 Townsend St.
Oakland, Calif. W. A. Hurst, R. 214 Easton Bldg.
Oakland, Calif. H. Bullard, 1788 Seventh St.
Oakland, Calif. E. W. Becker, 3357 East 14th St.
Livermore, Calif. C. Harlie Power.
San Jose, Calif. W. H. Turick, 275 So. First St.
Stockton, Calif. Conrad Mantele, 129 N. Sutter St.
Sacramento, Calif. H. T. Harger, 1022 "K" St.
Oroville, Calif. R. A. Williams
Portola, Calif. W. H. Morgan.

SPURS AND COMMERCIAL TRACKS
MAIN LINE

STATIONS	Distance from San Francisco	How Connected
KOHLER.....	11.6	1 W
HARVEY.....	12.8	1 E
HUDSON.....	15.9	1 E
ESTUDILLO.....	16.5	1 E
SORENSEN.....	22.1	1 W
ALVARADO JCT.....	24.9	Siding
PABRICO.....	27.5	1 W
EBERLY.....	28.9	Siding
ROCKMILL.....	30.8	1 E
RADUM.....	43.4	1 W
TREVARNO.....	49.0	1 W
REDMOND CUT.....	59.3	Siding
VALPICO.....	68.3	Siding
LUDWIG.....	73.0	1 E
RHODES.....	75.6	Siding
NILEGARDEN.....	82.8	1 W
FRENCH CAMP.....	88.6	1 W
HARTE.....	100.5	1 W
ALSCO.....	106.9	Siding
VILLINGER.....	107.8	1 W
LAS VINAS.....	109.5	Siding
BRADFORD.....	119.0	1 W
ALBERT.....	127.2	1 W
CORDOVA.....	133.7	1 E
BOMBAY.....	146.4	Siding
STRAUCH.....	148.4	1 E
CLEVELAND.....	176.2	1 W
GRAYBROS.....	187.7	1 W
VISTA ROBLES.....	198.8	1 E
ADELAIDE.....	202.7	1 E
LAND.....	212.1	Siding
LAS PLUMAS, F 2, 3 and 4.....	221.4	1 E
WEST FORK.....	222.3	1 E
BLINZIG, F 3 and 4.....	228.6	Siding
McLEAH.....	230.1	1 W
ISAH, F 3 and 4.....	230.5	1 W
CALIME.....	234.1	1 W
MAYARO, F 3 and 4.....	240.9	No Siding
ROCK CREEK, F 3 and 4.....	249.2	1 W
STORRIE, F 3 and 4.....	250.6	1 E
HOWELLS, F 3 and 4.....	261.8	Siding
SMITH'S POINT.....	264.5	No Siding
GRAY'S FLAT, F 3 and 4.....	272.6	1 W
CROMBERG, F 3 and 4.....	303.3	Siding
PENMAN.....	307.0	1 W
FEATHER RIVER INN.....	309.3	1 E
DELLEKER.....	320.0	1 E

RAILROAD SURGEONS

DR. A. R. KILGORE.....	Chief Surgeon.....	San Francisco
DR. E. S. KILGORE.....	Division Surgeon.....	San Francisco
DR. CURTIS E. SMITH.....	Assistant Division Surgeon.....	San Francisco
DR. G. F. CUSHMAN.....	Local Surgeon.....	San Francisco
DR. J. P. WARREN.....	Assistant Local Surgeon.....	San Francisco
DR. H. E. MILLER.....	Dermatologist.....	San Francisco
DR. GEORGE N. HOSFORD.....	Oculist.....	San Francisco
DR. MERTON PRICE.....	Aurist.....	San Francisco
DR. SUMNER EVERINGHAM.....	Local Surgeon.....	Oakland, Calif.
DR. T. ERIC REYNOLDS.....	Assistant Local Surgeon.....	Oakland, Calif.
DR. J. W. CALKINS.....	Oculist and Aurist.....	Oakland, Calif.
DR. CHANNING HALL.....	Local Surgeon.....	Berkeley, Calif.
DR. W. E. MITCHELL.....	Local Surgeon.....	San Leandro
DR. LUTHER MICHAEL.....	Local Surgeon.....	Hayward, Calif.
DR. R. M. MANSON.....	Local Surgeon.....	Niles, Calif.
DR. E. C. GRAU.....	Local Surgeon.....	San Jose, Calif.
DR. FRED S. RYAN.....	Local Surgeon.....	San Jose, Calif.
DR. H. G. ZANGER.....	Assistant Local Surgeon.....	Oakland, Calif.
DR. J. HAL COPE.....	Local Surgeon.....	Pleasanton, Calif.
DR. P. E. DOLAN.....	Local Surgeon.....	Livermore, Calif.
DR. ALLEN POWERS.....	Local Surgeon.....	Tracy, Calif.
DR. ELLIS HARBERT.....	Local Surgeon.....	Stockton, Calif.
DR. J. P. HULL.....	Assistant Local Surgeon.....	Stockton, Calif.
DR. BARTON J. POWELL.....	Oculist and Aurist.....	Stockton, Calif.
DR. DEWEY POWELL.....	Assistant Oculist and Aurist.....	Sacramento
DR. C. B. JONES.....	Local Surgeon.....	Sacramento
DR. S. J. WELLS.....	Assistant Local Surgeon.....	Sacramento
DR. G. A. FOSTER.....	Assistant Local Surgeon.....	Sacramento
DR. W. R. BRIGGS.....	Oculist and Aurist.....	Sacramento
DR. JNO. L. FANNING.....	Dermatologist.....	Sacramento
DR. G. W. STRATTON.....	Local Surgeon.....	Marysville, Calif.
DR. E. A. KUSEL.....	Local Surgeon.....	Oroville, Calif.
DR. B. J. LASSWELL.....	Local Surgeon.....	Quincy, Calif.
DR. W. M. EDWARDS.....	Division Surgeon.....	Portola, Calif.
DR. FRED J. DAVIS.....	Local Surgeon.....	Westwood, Calif.
DR. A. G. LEVIN.....	Assistant Local Surgeon.....	Westwood, Calif.

P. D. BARRY, Trainmaster, Stockton.
J. P. McSWEENEY, Trainmaster, Portola.
J. J. DUGGAN, Chief Train Dispatcher, Sacramento.
E. T. GALLAGHER, Night Chief Train Dispatcher, Sacramento.