

THE WESTERN PACIFIC RAILROAD CO.



WESTERN DIVISION



TIME 24 TABLE

In Effect 12:01 A. M. "Pacific" Time

SUNDAY, JUNE 12, 1938

This Time Table is for the exclusive use and guidance of the employes concerned. The Company reserves the right to vary from it at pleasure.

Always have the Book of Rules of the Transportation Department at hand for reference.

E. W. MASON,
Vice President and General Manager.

J. P. QUIGLEY,
Superintendent of Transportation.

J. H. LEARY,
Superintendent.

2 Eastward FIRST SUBDIVISION Westward

Fuel, Water, Fone, Table, Scale, Wye, Bulletin, Register Station, Standard Clock, Interlocking Plant.	SECOND CLASS		FIRST CLASS		Distance from San Francisco	Time Table No. 24		Distance from Stockton	FIRST CLASS		SECOND CLASS			Car Capacity of Sidings
						June 12, 1938								
	82	62	2			1	77		61	81				
	Fast Freight	Fast Freight	Scenic Limited		Scenic Limited	Fast Freight	Fast Freight	Fast Freight						
	Leave Daily	Leave Daily	Leave Daily		Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily						
W. F. O.			9.40 AM	0.0	DN SAN FRANCISCO	93.8	4.52 PM							
B. R. P. K.			10.00	3.5	DN OAKLAND PIER (S. P.)	90.3	4.32							
F. W. T. O.	9.45 PM	5.00 AM	10.10	5.5	DN OAKLAND YARD (W.P.)	88.8	4.15							
P. R. K.			Via S. P.	5.8	S. P. Crossing	88.0	Via S. P.			4.00 PM	9.00 PM	2.00 AM	Yard	
I.					CHESTNUT JUNCTION	87.95	4.08 PM							
R. I.			10.16 AM	5.85	S. P. Connection									
	9.50	5.05	s 10.28	6.6	OAKLAND	87.2	s 4.05			3.50	8.55	1.50		
				6.7	S. P. Crossing	87.1								
				7.2	S. P. Crossing	86.6								
I.				7.8	S. P. Crossing	86.0								
	10.02	5.20	f 10.38	9.6	FRUITVALE	84.2	f 3.50			3.30	8.40	1.35		
				10.3	S. P. Crossing	83.5								
I.				10.6	MELROSE	83.2								
P.	10.12	5.35		10.47	S. P. Crossing	80.8	3.41			3.10	8.28	1.20	38	
P.	10.16	5.40	f 10.50	14.8	D SAN LEANDRO	79.0	f 3.38			3.05	8.24	1.15		
P.	10.29	6.20	f 10.58	20.5	2S HAYWARD	73.8	f 3.30			2.50	8.10	12.55	89	
	10.42	6.40	11.07	26.6	DECOTO	67.2	3.22			2.30	7.50	12.35	18	
W. P.	11.05	7.23	f 11.14	29.7	DN NILES	64.1	f 3.17			2.20	7.43	12.25 AM	47	
I.				30.3	S. P. Crossing	63.5								
P. Y.	11.08	7.27	11.16	30.5	NILES JUNCTION	63.3	3.12			2.05	7.36	11.48 PM		
P.	11.28	7.52	11.26	36.0	SUNOL	57.8	3.04			1.40	7.24	11.28	79	
P.	11.41	8.17	f 11.34	41.5	D PLEASANTON	52.3	f 2.57			1.20	7.12	11.10	78	
I.				42.7	S. P. Crossing	51.1								
I.				43.0	S. P. Crossing	50.8								
W. P.	11.55 PM	8.44	f 11.44	47.3	D LIVERMORE	46.2	f 2.48			1.00	6.58	10.52	76	
P.	12.18 AM	9.16	11.58 AM	56.5	N ALTAMONT	37.8	2.36			12.35	6.38	10.31	53	
P.	12.33	9.33	12.07 PM	63.0	MIDWAY	30.8	2.22			12.07 PM	6.15	10.05	51	
W. Y. P.	12.51	10.05	12.17	71.8	D CARBONA	22.0	2.06			11.25 AM	5.43	9.29	53	
P. I.	12.55	10.12	12.20	73.9	D LYOTH	19.9	2.03			11.15	5.30	9.15	20	
P.	1.02	10.22	12.23	78.8	S. P. Crossing	17.0	1.59			11.05	5.20	9.07	89	
P. I.	1.19	10.45	12.32	83.8	FITZ	10.0	1.50			10.45	5.01	8.48	56	
P.	1.35	11.05	12.40	90.3	LATHROP	8.5	1.42			9.59	4.45	8.30	50	
F. W. T. O.	1.40 AM	11.10 AM	12.43	92.0	S. P. Crossing	1.8	1.39			9.45 AM	4.40 PM	8.25 PM	Yard	
P. B. R. K.	3.25 AM	12.55 PM		93.2	ORTEGA	0.6				7.00 AM	3.40 PM	7.25 PM		
I.				93.8	DN STOCKTON YARD	0.0	1.35 PM			6.45 AM	3.30 PM	7.15 PM		
P. R. K.	3.35 AM	1.05 PM	s 12.50 PM		A. T. & S. F. Crossing									
	Arrive Daily	Arrive Daily	Arrive Daily		DN STOCKTON		Leave Daily			Leave Daily	Leave Daily	Leave Daily		
	3.55	6.10	2.40		Time over Subdivision		2.40			6.15	4.20	5.35		
	22.1	14.0	33.9		Average Speed an Hour		33.9			13.9	19.9	15.5		

Yard Limits: Oakland, Niles, Carbona and Stockton. Oakland Yard extends from W. P. Mole to 500 feet east of east switch, Elmhurst. Stockton Yard extends from yard limit board at bridge 89.82 to yard limit board 19 1/2 poles east of M. P. 96.

See page 7 for speed restrictions.

Between Chestnut Jct. and Oakland Pier, trains will be governed by S. P. Time Table and Rules and Regulations of the Transportation Department.

Chestnut Jct. is initial station for No. 2.

Eastward W. P. trains originating at Oakland Pier must obtain W. P. clearance card at Oakland Pier and will not require clearance card at Chestnut Jct. unless train orders are received.

Trains originating and terminating at Oakland Pier will register by ticket at Chestnut Jct. to be placed on register at Oakland Yard by Operator. Other trains will not register at Chestnut Jct.

It will not be necessary to stop at S. P. Crossings M.P. 6.7, and M.P. 10.3. It will not be necessary to stop at S. P. Crossing M.P. 7.2 unless Crossing being used by a train or engine of that railroad.

No. 1 will register by ticket at Stockton Yard.

No. 2 will not register at Stockton Yard.

Operator at Stockton will transmit registration of No. 2 to Operator at Stockton Yard, who will enter on register, immediately verifying with Dispatcher, for information of trains originating at Stockton Yard.

At Stockton Yard, track 1, west switch at M. P. 91 and east switch 12 poles west of M. P. 92, is siding to be used when first class trains meet at Stockton Yard.

Westward freight trains will enter Stockton Yard at lead switch immediately west of South Street and eastward freight trains at lead switch M. P. 91. Track 9 will be used as run around track for movement of engines between round house and west end of yard.

Stockton Yard is the terminal for second class and extra trains, First and Second Subdivisions. At Stockton, second class and extra trains originating or terminating at Stockton Yard will not require clearance card unless train orders are received.

Stockton is register station for first class trains only.

Automatic Block System signals located as follows:
 Eastward: Home signals M. P. 29.4, M. P. 30.0 and M. P. 30.4.
 Westward: Distant signal M. P. 31.7; home signals M. P. 31.3 and M. P. 30.3.

Trains moving from San Jose Branch: Switch indicators located at head block of east and west main track wye switches govern trains from wye to main track.

East	
Fuel, Water, Fone, Table, Scale, Wye, Bulletin, Register Station, Standard Clock, Interlocking Plant.	Car Capacity of Sidings
P. R. K. I.	
I.	
P.	
P. Y.	
W. P.	
P.	
P.	
F. W. P. K.	
I.	38
R. I.	
O. Y. K. P. R.	89
I.	18
P.	47
P.	
I.	79
W. P.	78
P.	
P.	
W. P. I.	76
I.	53
I.	51
P.	53
P.	20
P.	89
F. W. T. O.	56
Y. B. R. K. P.	50
	Yard

Yard Lim extends from M. P. 96. Sacr to yard limit. limit board M yard limit bc

See page 7

6 Eastward FIRST SUBDIVISION "A"—SAN JOSE BRANCH. Westward

Fuel, Water, Pone, Table, Scale, Register Station, Standard Clock, Interlocking Plant	SECOND CLASS		Distance from Niles	Time Table No. 24 JUNE 12, 1938		Distance from San Jose Alameda St. Freight Station	SECOND CLASS		Car Capacity of Sidings
	282 Freight	Leave Daily		281 Freight	Arrive Daily				
W. P. R.	12.30 AM	0.0	DN	NILES	0.0	23.8	10.45 PM	47	
Y. P.	12.40	0.8		NILES JUNCTION	0.8	23.0	10.25		
P.	1.00	4.1		IRVINGTON	3.3	19.7	10.10	20	
	1.15	7.6		WARM SPRINGS	4.1	16.2	9.55	Spur 1W 6	
P.	1.35	11.7		MILPITAS	3.2	12.1	9.40	31	
	1.45	14.9		BERRYESSA	0.3	8.9	9.25		
		15.2		Peninsular R. R. Crossing	2.5	8.6			
P. K.	2.00	17.7		SAN JOSE		6.1	9.10		
P. W. T. F. E. B. O.	2.10 AM	18.3	D	East Santa Clara St.	0.6	5.5	9.00 PM	Yard	
		20.3		SAN JOSE YARD	2.0				
		20.4		S. P. TRANSFER	0.1	3.5			
		20.4		VALBRICK	0.6	3.4			
		21.0		S. P. CROSSING	2.1	2.8			
		23.1		S. P. CROSSING	0.7	0.7			
		23.8		SAN JOSE		0.0		Yard	
				Alameda St. Freight Station					
	Arrive Daily						Leave Daily		
	1.40			Time over Subdivision			1.45		
	11.0			Average Speed an Hour			10.5		

Yard Limits: Niles and San Jose. Niles yard extends to yard limit board 3000 feet east of wye switch at Niles Jct. San Jose yard extends to yard limit board M. P. 15.2. Junction and Niles. Their movement between these points will be governed by block signals and Rule 93. Time shown at Niles is for information only. San Jose Branch trains have no Time Table superiority between Niles Crossing at M. P. 15.2. Trains must stop at STOP board before passing over Peninsular Railroad

SPURS AND COMMERCIAL TRACKS

MAIN LINE			
STATIONS	Distance from San Francisco	How Connected	Car Capacity
HUDSON	15.9	1 E	14
ESTUDILLO	16.5	1 E	12
ALVARADO JCT.	24.9	Siding	40
PABRICO	27.5	1 W	30
EBERLY	28.9	Siding	31
RADUM	43.4	1 W	11
TREVARNO	49.0	1 W	13
REDMOND CUT	59.3	Siding	35
VALPICO	68.3	Siding	30
LUDWIG	73.0	1 E	11
RHODES	75.6	Siding	19
HARTE	100.5	1 W	7
ALSCO	106.9	Siding	20
VILLINGER	107.8	1 W	17
LAS VINAS	109.5	Siding	52
BRADFORD	119.0	1 W	...
ALBERT	127.2	1 W	10
CORDOVA	133.7	1 E	3
BOMBAY	146.4	Siding	13
CLEVELAND	178.2	1 W	16
GRAYBROS.	187.7	1 W	7
VISTA ROBLES	198.8	1 E	34
ADELAIDE	202.7	1 E	...
LAND	212.1	Siding	Yard
LAS PLUMAS	221.4	1 E	6
BLINZIG	228.6	Siding	13
McLEAN	230.1	1 W	1
ROCK CREEK	249.2	Siding	15
GRAY'S FLAT	272.6	1 W	70
CROMBERG	303.3	Siding	30
FEATHER RIVER INN	309.3	1 E	2
BOX	K15.4	1 W	34
BUTTE VALLEY LBR. CO.	K95.5	1 W	8

RAILROAD SURGEONS

DR. A. R. KILGORE	Chief Surgeon	San Francisco, Calif.
DR. E. S. KILGORE	Division Surgeon	San Francisco, Calif.
DR. CURTIS E. SMITH	Assistant Division Surgeon	San Francisco, Calif.
DR. G. F. OUSHMAN	Local Surgeon	San Francisco, Calif.
DR. GEORGE N. HOSFORD	Oculist	San Francisco, Calif.
DR. FRANK HAND	Aurist	San Francisco, Calif.
DR. SUMNER EVERINGHAM	Local Surgeon	Oakland, Calif.
DR. T. ERIC REYNOLDS	Assistant Local Surgeon	Oakland, Calif.
DR. FRANK S. BAXTER	Oculist and Aurist	Oakland, Calif.
DR. CHANNING HALL	Local Surgeon	Alameda, Calif.
DR. W. E. MITCHELL	Local Surgeon	Berkeley, Calif.
DR. LUTHER MICHAEL	Local Surgeon	San Leandro, Calif.
DR. R. M. MANSON	Local Surgeon	Hayward, Calif.
DR. E. C. GRAU	Local Surgeon	Niles, Calif.
DR. FRED S. RYAN	Local Surgeon	San Jose, Calif.
DR. H. G. ZANGER	Assistant Local Surgeon	San Jose, Calif.
DR. RICHARD HEINZ	Local Surgeon	Pleasanton, Calif.
DR. P. E. DOLAN	Local Surgeon	Livermore, Calif.
DR. ALLEN POWERS	Local Surgeon	Tracy, Calif.
DR. A. L. VAN METER	Local Surgeon	Stockton, Calif.
DR. J. P. HULL	Local Surgeon	Stockton, Calif.
DR. BARTON J. POWELL	Oculist and Aurist	Stockton, Calif.
DR. DEWEY POWELL	Assistant Oculist and Aurist	Stockton, Calif.
DR. A. M. HENDERSON, JR.	Local Surgeon	Sacramento, Calif.
DR. S. J. WELLS	Assistant Local Surgeon	Sacramento, Calif.
DR. W. R. BRIGGS	Oculist and Aurist	Sacramento, Calif.
DR. C. W. STRATTON	Local Surgeon	Marysville, Calif.
DR. E. A. KUSEL	Local Surgeon	Oroville, Calif.
DR. J. W. MOORE	Local Surgeon	Quincy, Calif.
DR. W. B. McKNIGHT	Division Surgeon	Portola, Calif.
DR. J. D. COULTER	Assistant Division Surgeon	Portola, Calif.
DR. W. E. BATSON	Local Surgeon	Greenville, Calif.
DR. FRED J. DAVIS	Local Surgeon	Westwood, Calif.
DR. A. G. LEVIN	Assistant Local Surgeon	Westwood, Calif.

WATCH INSPECTORS

S. A. Pope, Manager of Time Service, San Francisco.

San Francisco, Calif.	I. S. Preston, R. 210 Phelan Bldg.
San Francisco, Calif.	M. S. Grousd, 210 Townsend St.
Oakland, Calif.	E. S. Griffin, R. 214 Easton Bldg.
Oakland, Calif.	E. W. Becker, 3357 East 14th St.
Oakland, Calif.	H. Bullard, 1194 Seventh St.
Livermore, Calif.	O. Harlie Power
San Jose, Calif.	W. H. Turick, 275 So. First St.
Stockton, Calif.	Conrad Mantele, 129 N. Sutter St.
Sacramento, Calif.	H. T. Harger, 1022 "K" St.
Oroville, Calif.	R. A. Williams
Portola, Calif.	W. H. Morgan

Eastward FIRST SUBDIVISION "B"—CARBONA BRANCH. Westward

Fuel, Water, Pone, Table, Scale, Wye, Bulletin, Register Station, Standard Clock	Time Table No. 24 June 12, 1938		Distance from Carbona	Distance from Moy	Car Capacity of Sidings
	STATIONS Telegraph Offices and Calls				
W. Y. P.	0.0	D	CARBONA	0.0	77
	1.7		KERLINGER	2.5	Spur 1W 9
O. P.	3.4		RIVER ROCK	0.8	Spur 1W 52
	4.2		MOY	0.0	No Siding

Derails on main track M. P. 3.3 and 240 feet west and 885 feet east of Stock Yards Moy. Cars on main track east of River Rock not protected.

SECOND SUBDIVISION "A"—TERMINOUS BRANCH.

Eastward		Time Table No. 24 June 12, 1938		Westward	
Fuel, Water, Pone, Table, Scale, Wye, Bulletin, Register Station, Standard Clock	Distance from Terminous Jct.	STATIONS Telegraph Offices and Calls	Distance from Terminous	Car Capacity of Sidings	
	3.5	GARDEN	4.3	10	
	6.6	GRASS	1.2	6	
W. Y.	7.8	D	TERMINOUS	0.0	Yard

SPECIAL INSTRUCTIONS

SPEED RESTRICTIONS

SPEED RESTRICTIONS IN MILES AN HOUR WILL APPLY AS FOLLOWS:

Page	BETWEEN	Passenger		Freight	
		Maximum	Restriction	Maximum	Restriction
2	First Subdivision.....	60	..	40	..
	Over Interlocking Crossings.....	..	40	..	25
	Over, along or upon any of the public streets or highways within Oakland City limits.....	..	15	..	10
	Washington and Franklin Sts., Oakland..	..	8	..	8
	Approaching and passing over S.P. Crossing M.P. 7.2.....	..	15	..	15
	M.P. 9.5 just east 29th Avenue and M.P. 9.8 just east Fruitvale Avenue.....	..	10	..	10
	Approaching and passing over S. P. Crossing M.P. 10.3.....	..	15	..	15
	Bridge just west of Leandro Depot and Williams Street, 5 blocks east of depot..	..	20	..	15
	M.P. 23.93 and M.P. 24.31.....	..	35	..	25
	On Curve M.P. 29.4.....	..	40
	Niles and M.P. 37.....	..	45	..	30
	Through Tunnel 1.....	..	1 1/2 mins.	..	3 mins.
	Within City Limits Pleasanton and Livermore.....	..	15	..	15
	On Curves between M.P. 52 and M.P. 67.	..	45	..	30
	On Curves between M.P. 53.40 and M.P. 55.....	..	35	..	25
	On Curve at Bridge 56.96.....	..	45	..	35
	San Joaquin River Drawbridge M.P. 80.28	..	20	..	15
	A. T. & S. F. Crossing M.P. 93.2 and Stockton Depot.....	..	8	..	8
3	Second Subdivision.....	60	..	40	..
	Over Interlocking Crossings.....	..	40	..	25
	Stockton Depot and Park Street, Stockton	..	8	..	8
	Mokelumne River Drawbridge M.P. 116.4	..	20	..	20
	Bradford Spur.....	..	10	..	10
	M.P. 129 and 131.....	..	50	..	35
	"C" and "Y" Streets, Sacramento.....	..	15	..	15
	M. P. 152. 5, S. N. Crossing (See page 8)
	On Curve at Cleveland and at M.P. 186.5; between Graybros and M.P. 189 and on curve M.P. 201.9.....	..	50	..	35
	4	Portola and Keddie.....	40	..	30
Keddie and Las Plumas.....		35	..	25	..
Las Plumas and Oroville.....		40	..	30	..
Bridge 252.60.....		..	25	..	20
Over Switch East end Tunnel 32.....		..	20	..	20
Through Tunnel 35.....		..	2 mins.	..	4 mins.
On curve at M.P. 315 and on first curve east of M.P. 315.....		..	30	..	20
5	Keddie and Crescent Mills.....	25	..	25	..
	Crescent Mills and Greenville.....	40	..	40	..
	Greenville and Almanor.....	25	..	25	..
	Almanor and Red River Jct.....	40	..	25	..
	Red River Jct. and Mason.....	30	..	30	..
	Mason and Halls Flat.....	40	..	40	..
	Halls Flat and Pit River Station.....	30	..	30	..
	Pit River Station and Bieber.....	40	..	40	..
	On curves Red River Jct. and Westwood	..	25	..	25
	On curves between M.P. 88 and 95.....	..	25	..	25
On curve west mile board Willow Springs	15	
6	San Jose Branch.....	30	..	25	..
	Over Peninsular R.R. Crossing M.P. 15.2	..	6	..	6
	Within city limits, San Jose.....	..	12	..	12
	Over all street and highway crossings within city limits, San Jose and over Peninsular R.R. crossing San Carlos St. San Jose..	..	5	..	5
	Carbona Branch.....	12	..	12	..
	Terminus Branch.....
	Terminus Jct. and Garden.....	20	..	20	..
Garden and Terminus.....	15	..	15	..	

Maximum speed, trains handling steam derricks, steam shovels, cranes, rotary plows or pile drivers, 25 miles an hour on First and Second Subdivisions and 20 miles an hour on Third and Fourth Subdivisions.

Speed of engines backing must not exceed 20 miles an hour on straight track, on curves and where track conditions are unfavorable, speed must be reduced still further to a rate consistent with safety.

Maximum speed, Consolidation and Mikado engines handling passenger trains, 50 miles an hour.

Maximum speed, Mallet engines, M-80 Class; Third Subdivision 30 miles an hour; Fourth Subdivision, 35 miles an hour.

Maximum speed, Mallet engines, M-137-151 Class, 30 miles an hour, except a speed of 5 miles an hour must not be exceeded through cross-overs and turn-outs.

Engines running light on main track, must not exceed speed prescribed for freight trains.

Engines running light on branches must conform to speed prescribed for freight trains on each branch.

MISCELLANEOUS

GENERAL

WESTWARD TRAINS ARE SUPERIOR TO EASTWARD TRAINS OF THE SAME CLASS.

When double-heading and lead engine is to be cut off train, air will be set by lead engine and stop made before being detached, after which train engine will fully release air brakes and regain full working pressure before proceeding. When air connections have not been disturbed back of engine next to train, it will not be necessary to make rear end test as prescribed by Rule 1156.

When conditions are favorable and in judgment of Conductor it is safe to do so, run may be made for train inspection on freight and mixed trains on First and Second Subdivisions, from one water stop to next water stop, except a maximum distance of 70 miles must not be exceeded between inspections and when conditions are favorable and in judgment of Conductor it is safe to do so, run may be made on freight and mixed trains on Third and Fourth Subdivisions without stopping for train inspection for a maximum distance of 45 miles, except a standing car to car or careful rolling inspection must be made on westward freight and mixed trains at Blairsden, Two Rivers or Sloat and at Almanor and Greenville and on eastward freight and mixed trains at Keddie or at some point between Keddie and Spring Garden and at Halls Flat.

When Mallet or Mikado engines are in a train with another engine of any class, either in service or dead in train, they must be spaced at least ten cars apart.

At Oakland, Stockton, Sacramento and Marysville, City Ordinance forbids the use of engine whistle except when necessary.

Where train line has not been separated, air test as prescribed by Rule 1155 need not be made at Terminals.

Figures given for capacity of sidings and spurs is the number of cars averaging 48 feet in length that tracks will hold between clearance points, not including engines and cabooses.

FIRST SUBDIVISION

Street crossing Third and Broadway, Oakland, must not be blocked by passenger trains regardless of the number of cars in train.

Tracks between a point 100 feet west of the west line of Washington Street and 100 feet east of the east line of Franklin Street, Oakland, and Joint W. P. and S. P. drill track between Melrose and Elmhurst must not be used for meeting or passing trains.

Any engine or cars moved over spur serving California Packing Corporation near 85th Ave., Oakland, must be under control and highway traffic protected by member of crew.

At Hayward, mikado engines must not use Farm Products Co. and Poultry Producers spurs.

At Hayward, freight trains doing switching between 9:00 P. M. and 7:00 A. M., will leave train outside of limits of bonded rails operating crossing bells at "A," "B" and "C" streets and will use engine whistle and bell only when necessary to comply with the Rules.

Westward trains take full tank of water at Niles.

Headlights and markers must be burning through Tunnel 1.

At Hayward, Pleasanton and Livermore, east siding switch is west of passenger station.

Engines must not use tracks other than tracks 1 and 2 at Radum.

At Carbona, crossover switch located 700 feet east of station is the west siding switch.

SECOND SUBDIVISION

Engines and cars must be brought to a stop at Country Club Highway crossing on North Channel Line, Stockton, and must be preceded by flagman over crossing.

Bridge over Smith Canal, North Channel Line, Stockton, will not clear man on top of high car.

At Terminus Jct., road crossing No. 4-105.7 must not be blocked more than five minutes. When a train stops at Terminus Jct. and there are three brakemen in crew, one brakeman must protect this crossing during time train is not cut.

The first street crossing west of South Sacramento must not be blocked by freight trains taking water, oil, or doing work at South Sacramento between 7:00 A.M. and 6:00 P.M. Eastward freight trains will, when necessary to avoid blocking this crossing, leave train west of crossing while taking water or oil, or switching.

At Sacramento, westward passenger engines and trains must not leave Depot until engineer knows that wigwag on "K" Street is in motion and eastward passenger engines and trains must not leave Depot until engineer knows that wigwag on "J" Street is in motion. If wigwag fails to operate a member of crew must precede engine or train over crossing.

Engines must not go beyond frog on Cliff House spur Marysville.

JOINT TRACK MARYSVILLE—

Sacramento Northern trains operate over Western Pacific main track between Sacramento Northern connection with Western Pacific main track, located 356 feet east and 355 feet west of bridge 178.18, Yuba River, Marysville. Sacramento Northern freight trains operate over Western Pacific siding between west switch and switch leading to Sacramento Northern track opposite Western Pacific passenger station Marysville. These tracks are designated as Joint Tracks. Automatic Interlocking Signals governing Joint Track located as follows:

EASTWARD—Home Signal 789 feet west of bridge 178.18; normal position stop. Distant Signal 2500 feet west of Home Signal; normal position caution.

Home Signal 724 feet east of bridge 178.18; normal position proceed. Distant Signal 789 feet west of bridge 178.18; normal position caution.

WESTWARD—Home Signal east end of bridge 178.79; normal position proceed. Home Signal 724 feet east of bridge 178.18; normal position stop.

SWITCH INDICATORS located at west siding switch, at west end of main track switch leading to interchange track, at east end of main track switch leading to interchange tracks, at west end of crossover leading from main track to siding, and at east switch High Line Track, 1400 feet west of M. P. 180.

Derail switch, pipe connected and operated with main track switch, located on siding at Marysville, 193 feet east of west switch.

NORMAL POSITION OF SWITCHES.—Junction switches must be locked for Western Pacific main track when not in use.

No engine, car, motor or train of Western Pacific or Sacramento Northern shall be operated over railroad crossing located 752 feet east of bridge 178.18 where Western Pacific house track crosses Sacramento Northern track, without being brought to a stop at STOP board and preceded over crossing by a member of crew who shall determine first that it is safe to proceed. STOP boards located 100 feet each side of crossing. Sacramento Northern trains and yard motors must approach this crossing with caution and not move onto or over crossing until determined first that it is safe to proceed.

MOVEMENT OF TRAINS over Joint Track will be governed by Rule 663 and made in accordance with indication of block signals, regardless of right or class. All trains of both companies must approach and pass through limits of Joint Track with caution, not exceeding a speed of 15 miles an hour. In using Joint Track freight trains should avoid delays to other trains of either Company.

THIRD SUBDIVISION

Engines must not use siding at Blinzig. Water may be obtained at Blinzig.

Engines of M-137-151 class must not use spur at Belden and other engines must not use this spur beyond M. P. 260.

At Twain, the extreme west switch is west siding switch.

At Keddie, engines of M-137-151 class, must not use tracks other than main track, siding, house track and Fourth Subdivision lead, when it can be avoided. If necessary to use other tracks, movements must be protected in such a way that engines of this class will not meet or attempt to pass engines or cars on these tracks.

When calling in flagman from east on Fourth Subdivision at Keddie, enginemen will sound six long blasts of whistle.

Mallet and Mikado engines may use house track Blairsden. Trains setting out or picking up two or more cars on house track, the air must be coupled and operative.

Engines heavier than consolidation type must not go beyond sign on Graeagle Mill track, 1166 feet east of the Blairsden house track switch.

Movement over Mill track between Blairsden and Graeagle must be made with air coupled and operative.

Headlights and markers must be burning through Tunnels 4, 5, 23, 33 and 35.

FOURTH SUBDIVISION

When calling in flagman from east on Fourth Subdivision at Keddie, enginemen will sound six long blasts of whistle.

When cars are set out between Almanor and Greenville or between Halls Flat and Little Valley, in addition to provisions of Rule 840, unless there is a derail, lower car must be chained to rail and Dispatcher notified.

Headlights and markers must be burning through Tunnels 1, 2, 3, 6 and 8.

At Greenville, cross-over switch located opposite depot is the east siding switch.

Engines or cars must not be moved over Highway crossing on Box spur just east of Greenville, without being brought to a stop and Highway traffic protected in both directions, by a member of crew.

Trains or engines using main track over Veneer Plant crossing east of passenger station and Third Street crossing, west of passenger station, Westwood, will reduce speed sufficiently to be able to stop before striking anything that might be on, or is about to use these crossings and between the following times, movement over these crossings must be preceded by flagman:

11.30 a.m. and 11.40 a.m. 4.30 p.m. and 4.40 p.m.
12.20 p.m. and 12.30 p.m. 7.30 p.m. and 7.30 a.m.

Gate tender at Third Street crossing, on duty 9.30 a. m. until 5.30 p. m. daily, except Sunday.

Movement of trains and engines on tracks other than main track, over any crossings in Westwood Yard, must be preceded by flagman.

When trains meet at Westwood, crossings at Veneer Plant, east of passenger station and Third Street, west of passenger station, must not be blocked.

At Westwood, derail on west end R. R. L. Co. electric siding must be kept in derail position when cars are on siding; derail located ten feet west of west No. 1 track switch on lead; derails adjacent to main track on both legs of wye.

At Westwood, switch leading from west end of house track to gravel bin spur must be left lined for gravel bin spur to serve as derail.

At Westwood, Western Pacific mikado and mallet engines and Southern Pacific Co. engines of similar type and weight, must not use Fredonia track or Standard Oil spur. Standard Oil spur may be switched by placing four cars between engine and cars to be switched.

Water at Little Valley not suitable for human consumption. Water peddlers and gang water cars must not be filled at this point.

INTERLOCKING PLANTS AND SIGNALS

M.P. 5.2 Peralta Tower, S. P. Crossing. Interlocked. Home signals 225 feet east and 425 feet west of crossing. No distant signals. One yellow marker signal 1500 feet west of eastbound Home signal. Cars must not be left standing between Home signals unless coupled to other cars or engine standing outside of Home signal limits.

M.P. 5.8, M.P. 5.85 Magnolia Tower, S. P. Crossings. Interlocked. Two-arm

Home signal 700 feet west of S. P. Crossing; upper arm governs movement main track over S. P. crossing eastward; lower arm governs movement main track over S. P. crossing to North track eastward. Dwarf signal 490 feet west of S. P. crossing governs movement track 1 over S. P. crossing to main track or North track eastward. Bracket signal 750 feet east of S. P. crossing; arm to right governs movement North track over Chestnut Jct. to S. P. or over S. P. crossing to W. P. freight yards westward; arm to left governs movement main track over Chestnut Jct. to S. P. westward. Suspended signal under main track signals governs movement main track over S. P. crossing and to W. P. freight yards westward. No distant signals.

S. P. crossing M.P. 6.7. Not interlocked. (See footnote, page 2).
S. P. crossing M.P. 7.2. Not interlocked. (See footnote, page 2).
M.P. 7.8 Clinton Tower, S. P. crossing. Interlocked. Home signals 450 feet east and west of crossing. One distant signal 2000 feet east of home signal.
S. P. crossing M.P. 10.3. Not interlocked.
M.P. 10.6 and M.P. 10.7 Melrose Tower, S. P. crossing. Interlocked. Home signals 450 feet west of crossing M.P. 10.6. Distant signal 2000 feet west of home signal. Home signal 685 feet east of crossing M.P. 10.7. Distant signal 2500 feet east of home signal.
S. P. crossing M.P. 13.7. Not interlocked.
M.P. 30.3 Niles Tower, S. P. crossing. Interlocked. Home signals 450 feet east and west of crossing. Distant signals 2380 feet east and 1379 feet west of home signals.
M.P. 42.7 and M.P. 43.0 Radum Tower, S. P. crossings. Interlocked. Towerman on duty from 9.00 a. m. until 6.00 p. m. daily except Sunday. During these hours, signals will be operated by Towerman in accordance with Rules 600 to 686-A inclusive. During hours when there is no towerman on duty, normal position of signals governing W. P. trains over these crossings will be proceed.

Home signals 480 feet east of crossing at M. P. 43.0 and 480 feet west of crossing at M. P. 42.7. Distant signals 2000 feet east and west of home signals. Switch indicator located at west switch Radum gives warning of approach of train in either direction. See Rule 512.

M.P. 73.9 Lyoth Tower, S. P. crossing. Interlocked. Home signal 800 feet west of crossing. Distant signal 2658 feet west of home signal. Home signal 600 feet east of crossing. Distant signal 2766 feet east of home signal. Two-arm home signal 210 feet west of crossing. Upper arm governs main track westward over cross-over switch; lower arm governs movement from main track through cross-over to siding. Dwarf signal, located between main track and interchange track 230 feet west of main track switch, governs movement from siding to main track.

M.P. 83.8 Lathrop Tower, S. P. crossing. Interlocked. Home signals 650 feet east and west of crossing. Distant signals 2640 feet east and 2914 feet west of home signals.

M.P. 90.3 Ortega Tower, S. P. crossing. Interlocked. Towerman on duty 6.00 p.m. until 3.00 a.m. Home signal 230 feet west and 450 feet east of crossing, Hunter Street track, governs movement over S. P. crossing. No distant signals. Trains or engines moving westward from Hunter Street track must not foul W. P. main track and W. P. main track junction switch must not be opened until it has been ascertained from Dispatcher, through Operator Stockton Yard that it is safe to do so. Telephone located near main track junction switch for this purpose. Trains and engines on main track must approach Ortega with CAUTION.

M.P. 93.2 A. T. & S. F. Tower, A. T. & S. F. Crossing. Interlocked. Home signals 450 feet east and west of crossing. One distant signal 2450 feet west of crossing. Tower is equipped with electric siren. Two short blasts repeated several times, is warning to yard and trainmen to clear plant.

M.P. 93.8 Weber Avenue Tower, S. P. crossing. Interlocked. Home signals 450 feet east and west of crossing. No distant signals.

M.P. 95.1 El Pinal Tower, S. P. crossing. Interlocked. Home signals 650 feet east and west of crossing. One distant signal 3000 feet east of home signal.

M.P. 137.5 "X" Street, C. C. T. and S. N. crossing. Automatic interlocked. Home signals 450 feet east and west of crossing. One distant signal 1480 feet west of home signal. Switch indicator located at head block of west switch old Ice House track, Sacramento, governs movement from old Ice House track to main track. Hayes derail on old Ice House track, 171 feet east of west switch, is pipe connected to main track switch and switch must not be closed until rear of train has passed derail. Maximum speed, 15 miles an hour within limits of home signals. Cars must not be left standing between home signal limits unless coupled to other cars or an engine standing outside of limits. Traveling cranes must not pass over this crossing unless coupled to one or more cars. If signal in STOP position, be governed by Rule 663.

M.P. 138.0 "R" Street Tower, S. P. crossing. Interlocked. Trains governed by two-arm home signals located 796 feet east and 700 feet west of crossing. Upper arms govern main track, lower arms govern legs of wye. No distant signals. Following are whistle signals: Main line to wye, either leg, one long, one short. Wye to main line, either leg, one short, one long.

M.P. 139.2 "C" Street, S. N. crossing. Automatic interlocked. Home signals 480 feet east and 450 feet west of crossing. No distant signals. Switch indicator located at head block of Haggin Transfer main track switch, just east of subway, Sacramento, governs movement from Haggin Transfer track to main track. Hand-operated derail on Haggin Transfer track, located 150 feet east of west switch, when not being used must be in derailing position. Maximum speed, 15 miles an hour within limits of home signals. Cars must not be left standing between home signal limits unless coupled to other cars or an engine standing outside of limits. If signals are in STOP position be governed by Rule 663.

S. N. crossing M.P. 140.8. Not interlocked.
M.P. 152.5 Sankey. S. N. crossing. Automatic interlocked. Home signals 600 feet east and west of crossing. Distant signals 3000 feet east and west of home signals.
Normal indication of home signals STOP, and when train enters approach circuit,

J. P. McSWEENEY, Trainmaster, Oakland.
P. D. BARRY, Trainmaster, Stockton.
J. J. DUGGAN, Trainmaster, Keddie.

home and distant signals should change to proceed. Speed of engine handling passenger train must not exceed 30 miles an hour, consuming not less than 14 seconds between home signal and crossing. Speed of engine handling freight train must not exceed 25 miles an hour, consuming not less than 16 seconds between home signal and crossing. When distant signal is at CAUTION positive action must be taken before passing such signal to control speed of train in conformity with Rule 603, Figure 3. If no cause for signals being at STOP is seen, flagman must be sent ahead to operate clockwork time release located in box at crossing which is secured with switch lock, instructions for which are inside of box and are as follows:

(a) Release must not be operated when trains or engines are between home signals or seen to be approaching on intersecting track.

(b) To operate clockwork time release, turn knob to right to extreme position, then let go of knob and allow automatic release mechanism to run down, which will require four minutes. When knob is turned to extreme position and release mechanism starts to operate, a red pilot light, located near clock release, should light immediately indicating that home signals on intersecting line are in STOP position. In meantime clockwork time release will run down and home signal should change from STOP to PROCEED WITH CAUTION and flagman will remain at crossing until train arrives. In case pilot light fails to appear, movement must be protected in each direction on intersecting line.

(c) In case operation of release does not change home signal indication from STOP to PROCEED WITH CAUTION after pre-determined time has elapsed, a repeater red indicator light located at home signal should then light up, indicating home signals on intersecting line are in STOP position.

JOINT TRACK MARYSVILLE (See special instructions Page 7, Second Sub-division).

M.P. 179.1 9th Street Tower, S. P. crossing. Interlocked. Home signals 414 feet east and 474 feet west of crossing. Distant signal 1040 feet west of home signal. Distant signal located on two-arm signal, 1210 feet east of home signal. Home signal 1624 feet east of crossing, protects movement over main track to and from High Line and S. P. interchange tracks. Distant signal 2582 feet east of home signal. Switch and derail to S. P. interchange track, switch and derail to High Line track and derail on stock yard track are hand operated and electrically locked and permission must be obtained from Towerman, when on duty, for each movement made in or out of these tracks. Towerman on duty 7.00 A. M. until noon and 1.00 P. M. until 4.00 P. M. When Towerman off duty, eastward trains desiring to use interchange track, must come to STOP immediately east of westward home signal, as electric locks cannot be released unless this is done. A member of crew must then operate hand time release located opposite two main track switches leading to High Line and S. P. interchange tracks. After time release returns to normal position, indicator lamp located in time release box should light up. When this light appears, all electric locks are released. Switches and derrails must be returned to normal position immediately after movement is made.

M.P. 180.2 Binney Jet. Tower, S. P. crossing. Interlocked. Home signals 650 feet east and west of crossing. Distant signals 3100 feet east and 2650 feet west of home signals.

KEDDIE YARD, Third and Fourth Subdivisions. Interlocked. Signals when in STOP position must not be passed except as prescribed by Rule 663 and as provided herein. Signals located as follows:

THIRD SUBDIVISION.—

EASTWARD: One unit three-position signal, M. P. 279.54; colors red, yellow and green. Two unit, two-position signal, M. P. 280.34. Upper unit governs over main track, Third Subdivision; colors red and green. Lower unit governs over main track, Third Subdivision to west leg of wye, Fourth Subdivision; colors red and yellow.

NOTE: Trains must not pass this signal unless signal light indications for main track movement Third Subdivision are: A green signal light above a red signal light. For movement over main track, Third Subdivision to west leg of wye, Fourth Sub-division, a yellow signal light below a red signal light, except as prescribed by Rule 663.

WESTWARD: One unit three-position signal, M. P. 280.65; colors red, green and yellow. One unit two-position signal, M. P. 280.52; colors red and green.

FOURTH SUBDIVISION.—

EASTWARD: One unit three-position signal, 50 feet east of Tunnel 1; colors red, yellow and green. One unit two-position signal, 125 feet east of Tunnel 1 on east leg of wye; colors red and green. One unit two-position signal, 242 feet west of east wye switch on west leg of wye; colors red and green.

WESTWARD: One unit three-position signal, M. P. 1.08; colors, red, yellow and green. Three-unit signal, 60 feet east of east wye switch. Upper unit, three positions, governs over west leg of wye towards main track, Third Subdivision; colors red, yellow and green. Middle unit, two positions, governs over east leg of wye through Tunnel 1; colors red and yellow. Lower unit, two positions, governs handling of helpers when to be cut into train which is occupying either east or west leg of wye; colors red and yellow.

NOTE: Trains requiring helper engine to be cut in train, that portion of train which is to be handled ahead of helper must be moved east of signal located 60 feet east of wye switch in order that operator may handle switches and signals to permit helper to be cut into train. In such cases, it will be necessary to flag helper engine past signal and over switch. Helper must also move to a point beyond signal located 60 feet east of wye switch, so operator can again handle switches and signal to permit helper engine and head end of train to be coupled. Before making a move of this kind, operator must be kept advised by telephone of movements required. Extreme care must be exercised in making this movement. Except where helpers are to be cut into train, trains must not pass this signal unless signal light indications are—

For movement over west leg of wye, green or yellow signal indication above two red signal indications. For east leg of wye, a yellow signal indication between two red

signal light indications. For east or west leg of wye when helper engine is to be cut into train, a yellow signal indication below two red signal indications.

One unit two-position signal, located 225 feet east of Third Subdivision junction switch on west leg of wye; colors red and green.

Switch located on main track, Third Subdivision, east of Tunnel 32 and switch at east end of wye, Fourth Subdivision, are interlocked. These switches are dual control and can be operated by hand or by power through operator at station. Each switch machine has one selector lever marked "Motor" and one hand-throw lever marked "N." Selector lever marked "Motor" is locked with switch lock. In case necessary to operate by hand, first unlock selector lever marked "Motor" and turn handle to hand operating position. This cuts off power. Then throw hand-throw lever marked "N" and if this lever is in proper position switch points will move instantly. After using switch, throw hand-throw lever marked "R," so lever is down in its stand in either normal or reverse position then throw selector lever marked "Hand" to "Motor" position. Inspect switch points to be sure they are lined properly and replace switch lock. In case switch lock rods are out of adjustment, preventing locking of switch, switch may be operated by hand but stroke of hand-throw lever cannot be completed and selector lever cannot be returned to "Motor" position. In cases of this kind, before train is allowed to pass over switch, switch points must be spiked in proper position.

At west end of Keddie Yard, a westward movement must not be made from Fourth Subdivision lead through crossover lead to Third Subdivision main track without first getting permission from operator at station.

A westward movement must not be made from siding to Third Subdivision main track, neither must crossover be fouled without first getting permission from operator at station.

Telephones located at or near all signals and at east end of Tunnel 32, are for obtaining information from operator at station.

Trains finding signals in STOP position or signal lights not burning, must get in communication with operator immediately, and be governed by Rule 663.

FOURTH SUBDIVISION

M.P. 8.38, I. V. R. R. crossing. Not interlocked.
M.P. 8.39, I. V. R. R. crossing (Standard Oil Spur). Not interlocked. See special instructions Page 5.

SAN JOSE BRANCH

M.P. 15.2, Peninsular R. R. crossing. Not interlocked.
M.P. 20.4, S. P. crossing. Not interlocked.
M.P. 21.0 Willow Glenn, S. P. crossing. Interlocked. Semi-automatic home signals 225 feet east and west of crossing. Normal position STOP. No distant signals.
M.P. 23.1 West San Jose, S. P. crossing. Interlocked. Home signals 250 feet east and west of crossing. Normal position STOP. No distant signals.

All trains must come to STOP at home signals, Willow Glenn and West San Jose crossings and a member of crew go to crossing and carefully follow instructions pasted in inside of derail lock box at each crossing before proceeding over either crossing.

TUNNEL SIGNALS

Automatic Block System signals govern movement through Tunnels 1, 2, 4 and 35 on First and Third Subdivisions.

Tunnels 1 and 2. Home signal 1500 feet west of west portal Tunnel 1. No distant signal. Home signal 200 feet east of east portal Tunnel 2. Distant signal 1800 feet east of home signal.

Tunnel 4. Home signals 1716 feet east and 1150 feet west of Tunnel. No distant signals.

Tunnel 35. Home signals 400 feet east and 1000 feet west of Tunnel. One distant signal 2000 feet east of home signal.

DRAWBRIDGE SIGNALS

San Joaquin River drawbridge M.P. 80.28. Interlocked. Home signals 650 feet east and 600 feet west of bridge indicate position of draw. Distant signals 2011 feet east and 2012 feet west of home signals.

Mokelumne River drawbridge M.P. 116.4. Interlocked. Home signals 500 feet east and west of bridge indicate position of draw. One yellow marker signal 1993 feet west of home signal.

TONNAGE RATING

EASTWARD Engine Class	1st Sub-division	2nd Sub-division	3rd Sub-division	4th Subdivision		
				Keddie to Greenville	Greenville to Almanor	Almanor to Bieber
TP-29.....	1073	2200	812	585	401	585
MTP-44.....	2000	5400				
C-43.....	1650	5000	1250	900	617	900
MK-60.....	2500	6000	1800	1250	858	1250
M-80.....			2200	1690	1170	1690
M-137-151..			4000			
WESTWARD				Bieber to Halls Flat	Halls Flat to Keddie	
TP-29.....	910	2200	*	491	1040	
MTP-44.....	1800	5400	*			
C-43.....	1400	5000	*	756	1600	
MK-60.....	2350	6000	*	1051	2200	
M-80.....			*	1427	3200	
M-137-151..			*			

*Descending grade, no tonnage limit.
Add five tons friction for each car over 30 cars.
Tonnage rating based on maximum grade each subdivision; between points where grades are less than maximum, greater tonnage can be handled.

C. D. JORZ, Night Chief Train Dispatcher, Sacramento.
G. L. HARLAN, Night Chief Train Dispatcher, Sacramento.